



US010755241B2

(12) **United States Patent**
Langschaedel et al.

(10) **Patent No.:** **US 10,755,241 B2**
(45) **Date of Patent:** **Aug. 25, 2020**

(54) **HOT WALLET FOR HOLDING BITCOIN**

(56) **References Cited**

(71) Applicant: **Coinbase, Inc.**, San Francisco, CA (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Julian Langschaedel**, Essen (DE);
Brian D. Armstrong, Beaverton, OR
(US); **Fred E. Ehram**, San Francisco,
CA (US)

2,634,738 A 4/1953 Fuller et al.
5,884,274 A 3/1999 Walker et al.
(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Coinbase, Inc.**, San Francisco, CA (US)

EP 2634738 9/2013
JP 2007-109002 A 4/2007
WO 2014190323 A1 11/2014

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 678 days.

OTHER PUBLICATIONS

(21) Appl. No.: **14/660,418**

Computer Arch (<http://www.math.uaa.alaska.edu/~afkjm/cs101/handouts/ComputerArch.pdf>, dated Sep. 10, 2009, attached as PDF file (Year: 2009).*

(22) Filed: **Mar. 17, 2015**

(Continued)

(65) **Prior Publication Data**

US 2015/0262176 A1 Sep. 17, 2015

Primary Examiner — James D Nigh

Assistant Examiner — Margaret M Neubig

(74) *Attorney, Agent, or Firm* — Jeffrey Schox; Diane Lin

Related U.S. Application Data

(60) Provisional application No. 62/099,992, filed on Jan. 5, 2015, provisional application No. 62/086,669, filed (Continued)

(51) **Int. Cl.**
G06Q 20/06 (2012.01)
G06Q 20/36 (2012.01)
(Continued)


(52) **U.S. Cl.**
CPC **G06Q 20/065** (2013.01); **G06Q 20/0658**
(2013.01); **G06Q 20/16** (2013.01);
(Continued)

(58) **Field of Classification Search**
USPC 705/50–79
See application file for complete search history.

(57) **ABSTRACT**

A system and method for transaction bitcoin is described. Bitcoin can be sent to an email address. No miner's fee is paid by a host computer system. Hot wallet functionality is provided that transfers values of some Bitcoin addresses to a vault for purposes of security. A private key of a Bitcoin address of the vault is split and distributed to keep the vault secure. Instant exchange allows for merchants and customers to lock in a local currency price. A vault has multiple email addresses to authorize a transfer of bitcoin out of the vault. User can opt to have private keys stored in locations that are under their control. A tip button rewards content creators for their efforts. A bitcoin exchange allows for users to set prices that they are willing to sell or buy bitcoin and execute such trades.

8 Claims, 76 Drawing Sheets



Related U.S. Application Data

on Dec. 2, 2014, provisional application No. 62/056,100, filed on Sep. 26, 2014, provisional application No. 62/042,676, filed on Aug. 27, 2014, provisional application No. 61/990,017, filed on May 7, 2014, provisional application No. 61/954,434, filed on Mar. 17, 2014.

(51) Int. Cl.

G06Q 20/38 (2012.01)
G06Q 20/16 (2012.01)
G06Q 40/04 (2012.01)
G06Q 20/40 (2012.01)
H04L 12/58 (2006.01)

(52) U.S. Cl.

CPC **G06Q 20/36** (2013.01); **G06Q 20/363** (2013.01); **G06Q 20/3678** (2013.01); **G06Q 20/381** (2013.01); **G06Q 20/382** (2013.01); **G06Q 20/388** (2013.01); **G06Q 20/3825** (2013.01); **G06Q 20/3829** (2013.01); **G06Q 20/40** (2013.01); **G06Q 20/4014** (2013.01); **G06Q 40/04** (2013.01); **H04L 51/08** (2013.01); **G06Q 2220/00** (2013.01)

(56)**References Cited****U.S. PATENT DOCUMENTS**

- 5,952,683 A 9/1999 Sakata et al.
6,125,186 A * 9/2000 Saito H04L 29/06
380/260
6,959,394 B1 * 10/2005 Brickell G06Q 20/206
380/44
7,644,037 B1 1/2010 Ostrovsky
7,689,500 B2 3/2010 Cottrell
7,689,550 B2 3/2010 Cottrell
7,970,823 B2 6/2011 Moeller et al.
8,055,575 B2 11/2011 Grody et al.
8,117,648 B2 2/2012 Slaton et al.
8,606,703 B1 12/2013 Dorsey et al.
8,839,386 B2 9/2014 Gilboy
9,135,787 B1 9/2015 Russell et al.
9,224,262 B2 12/2015 Fine et al.
9,495,668 B1 11/2016 Juels
9,892,460 B1 * 2/2018 Winklevoss G06Q 40/04
10,068,228 B1 9/2018 Winklevoss et al.
10,256,983 B1 4/2019 Bauer et al.
10,469,309 B1 11/2019 Gupta et al.
2001/0034605 A1 10/2001 Hoffman
2001/0050990 A1 * 12/2001 Sudia G06Q 20/3829
380/286
2002/0023053 A1 2/2002 Szoc et al.
2006/0168663 A1 7/2006 Viljoen et al.
2008/0091586 A1 4/2008 Cottrell
2009/0037405 A1 2/2009 Lee et al.
2009/0144810 A1 6/2009 Gilboy
2009/0205036 A1 8/2009 Slaton et al.
2011/0071958 A1 3/2011 Grody et al.
2011/0087582 A1 4/2011 Pak et al.
2011/0106675 A1 5/2011 Perlman
2011/0251941 A1 10/2011 Dunwoody
2012/0136782 A1 5/2012 Norman et al.
2012/0150750 A1 6/2012 Law et al.
2012/0239556 A1 9/2012 Magruder et al.
2013/0065670 A1 * 3/2013 Michaelson G06Q 20/0655
463/25
2013/0166455 A1 6/2013 Feigelson
2013/0290710 A1 10/2013 Broder et al.
2013/0343546 A1 12/2013 Shibutani et al.
2014/0025473 A1 1/2014 Cohen
2014/0052617 A1 2/2014 Chawla et al.
2014/0057599 A1 2/2014 Hazari
2014/0082749 A1 3/2014 Holland et al.

- 2014/0108223 A1 4/2014 Xiao
2014/0156512 A1 6/2014 Rahman et al.
2014/0172633 A1 6/2014 Dogin et al.
2014/0229739 A1 8/2014 Roth et al.
2014/0274327 A1 9/2014 Fine et al.
2014/0279436 A1 9/2014 Dorsey et al.
2015/0033301 A1 * 1/2015 Pianese H04L 63/10
726/5
2015/0050987 A1 2/2015 Huang et al.
2015/0120569 A1 4/2015 Belshie
2015/0127495 A1 5/2015 Houry
2015/0170112 A1 6/2015 DeCastro
2015/0178693 A1 6/2015 Solis
2015/0209678 A1 7/2015 Edwards et al.
2015/0220928 A1 8/2015 Allen
2015/0227897 A1 8/2015 Loera
2015/0262139 A1 9/2015 Shtulman
2015/0262171 A1 9/2015 Langschaedel et al.
2015/0262173 A1 9/2015 Durbin et al.
2015/0365283 A1 12/2015 Ronca et al.
2016/0034896 A1 2/2016 O'Brien et al.
2016/0085955 A1 3/2016 Lerner
2016/0086418 A1 3/2016 Smolen
2016/0171570 A1 6/2016 Dogin et al.
2016/0203572 A1 7/2016 McConaghy et al.
2016/0261411 A1 9/2016 Yau et al.
2016/0277398 A1 9/2016 Gregg et al.
2016/0321654 A1 11/2016 Lesavich et al.
2016/0380767 A1 12/2016 Hayashi et al.
2017/0063531 A1 3/2017 Sullivan
2017/0161439 A1 6/2017 Raduchel et al.
2018/0075453 A1 3/2018 Durvasula et al.
2018/0191503 A1 7/2018 Alwar et al.
2018/0248704 A1 8/2018 Coode et al.
2018/0367316 A1 12/2018 Cheng et al.
2019/0236245 A1 8/2019 Desarzens et al.

OTHER PUBLICATIONS

- Bitcoin Explained Like You're Five Part 3—Cryptography, captured by Wayback Machine on Oct. 25, 2013, attached as PDF file (Year: 2013).*
- Bitcoin Explained Like You're Five: Part 4—Securing Your Wallet, ('BC4', downloaded from <https://chrispacia.wordpress.com/2013/09/29/bitcoin-explained-like-youre-five-part-4-securing-your-wallet/> and attached as PDF file (Year: 2013).*
- Bitcoin Explained Like You're Five: Part 3—Cryptography ('BC3', downloaded from <https://chrispacia.wordpress.com/2013/09/07/bitcoin-cryptography-digital-signatures-explained/> and attached as a PDF file) (Year: 2013).*
- Beal, "Backing up sensitive data with secret sharing", downloaded from <http://www.usrsb.in/secret-sharing-backup.html> and attached as a PDF file. (Year: 2013).*
- Bitcoin Explained Like You're Five: Part 4—Securing Your Wallet ('BC4', downloaded from <https://chrispacia.wordpress.com/2013/09/29/bitcoin-explained-like-youre-five-part-4-securing-your-wallet/> (Year: 2013).*
- Coin Selection Algorithm, downloaded from <https://web.archive.org/web/20130228073524/https://bitcoin.stackexchange.com/questions/1077/what-is-the-coin-selection-algorithm> dated Feb. 27, 2014 and attached as a PDF file (Year: 2014).*
- Bitcoin Explained Like You're Five: Part 4—Securing Your Wallet ('BC4', downloaded from <https://chrispacia.wordpress.com/2013/09/29/bitcoin-explained-like-youre-five-part-4-securing-your-wallet/> (Year: 2013) (Year: 2013).*
- Coin Selection Algorithm, downloaded from <https://web.archive.org/web/20130228073524/https://bitcoin.stackexchange.com/questions/1077/what-is-the-coin-selection-algorithm> dated Feb. 27, 2014 and attached as a PDF file (Year: 2014) (Year: 2014).*
- Beal, "Backing up sensitive data with secret sharing", downloaded from <http://www.usrsb.in/secret-sharing-backup.html> and attached as PDF file previously (Year: 2013).*
- Strongcoin (NPL PDF file attached, downloaded from Wayback <https://web.archive.org/web/20130120011013/https://www.strongcoin.com/?locale=en> (Year: 2013).*

(56)

References Cited**OTHER PUBLICATIONS**

<https://github.com/trottier/original-bitcoin/blob/master/src/main.cpp> for SelectCoin code, lines 2410-2510, attached as PDF file; dated Apr. 4, 2013 (Year: 2013) (Year: 2013).*

Bitcoin Explained Like You're Five: Part 3—Cryptography ('BC3', downloaded from <https://chriscapcia.wordpress.com/2013/09/07/bitcoin-cryptography-digital-signatures-explained/> and attached as a PDF file) (Year: 2013) (Year: 2013).*

Computer Arch (<http://www.math.uaa.alaska.edu/~afkjm/cs101/handouts/ComputerArch.pdf>, dated Sep. 10, 2009, attached as PDF file (Year: 2009) (Year: 2009).*

NIST (Archived NIST Technical Series Publication, dated Jul. 2012, "nistspecialpublication800-57p1r3", attached as a PDF file (Year: 2012).*

"A plea to exchanges . . . lets do 2 factor right!", Bitcoin Forum, download from <https://bitcointalk.org/index.php?topic=109424.0%20%E2%80%93Stephen%20Gornick%20NOV%205%20%2712%20at%2016:56> (posted Sep. 14, 2012), (10 pages).

"Bitcoin Explained", <https://chriscapcia.wordpress.com/2013/09/29/bitcoin-explained-like-you-re-five-part-4-securing-your-wallet/>, (12 pages).

"Bitcoin Explained Like You're Five, Part 4—Securing Your Wallet", <https://chriscapcia.wordpress.com/2013/09/29/bitcoin-explained-like-youre-five-part-4-securing-your-wallet/>, dated Sep. 29, 2013) (Year: 2013), (15 pages).

"BlockchainCreate", <http://blockchain.info:80/wallet/faq>, dated Jan. 9, 2012, (5 pages).

Final Office Action dated Feb. 2, 2018, U.S. Appl. No. 14/660,307, (40 pages).

Final Office Action dated Jan. 16, 2018, U.S. Appl. No. 14/660,296, (48 pages).

Final Office Action dated Sep. 26, 2017, U.S. Appl. No. 14/660,014, (63) pages.

International Search Report and Written Opinion dated Jul. 31, 2015, International Patent Application no. PCT/US15/20840 with International Filing Date of Mar. 16, 2015, (11 pages).

Non Final Office Action dated Oct. 4, 2017, U.S. Appl. No. 14/660,331, (31 pages).

Non Final Office Action dated Aug. 24, 2017, U.S. Appl. No. 14/660,307, (39 pages).

Non Final Office Action dated Aug. 24, 2017, U.S. Appl. No. 14/660,296, (41 pages).

Non Final Office Action dated Feb. 6, 2018, U.S. Appl. No. 14/660,331, (31 pages).

Non Final Office Action dated Jan. 11, 2018, U.S. Appl. No. 14/660,427, (25 pages).

Non Final Office Action dated Jun. 1, 2017, U.S. Appl. No. 14/660,014, (42 pages).

Non Final Office Action dated Oct. 27, 2017, U.S. Appl. No. 14/660,440 filed Mar. 17, 2015, (26 pages).

Non Final Office Action dated Oct. 31, 2017, U.S. Appl. No. 14/660,422, (31 pages).

"Off-the-chain transactions", downloaded from <http://gavintech.blogspot.com/2012/07/off-chain-transactions.html>, dated Jul. 3, 2012 (Year: 2012) ., (4 pages).

"Securing your wallet", download from <https://bitcoin.org/en/secure-your-wallet> (post from 2013), (4 pages).

"Transaction Fees ("Transaction fees and negative balances"", downloaded from <https://bitcointalk.org/index.php?topic=6856.0>, dated Apr. 30, 2011-May 1, 2011, (Year: 2011), (3 pages).

"Wholesale Payment Systems: Interbank Payment and Messaging System, Fedwire and Clearing House Interbank Payment Systems (CHIPS)", <http://www.fiec.gov/fiecinfbase/booklets/Wholesale/02.html>, Dec. 16, 2005, (3 pages).

Beal, Alex , "Backing Up Sensitive Data Wth Secret Sharing", downloaded from <http://www.usrsb.in/secret-sharing-backup.html> , dated Feb. 23, 2013) (Year: 2013), (8 pages).

Dion, Derek A. , "I'll gladly trade you two bits on Tuesday for a byte today: Bitcoin, regulating fraud in the e-economy of Hacker-cash", Journal of Law, Technology & Policy, vol. 2013, 2013, pp. 165-201.

Doguet, Joshua J. , "The Nature of the Form: Legal and Regulatory issues surrounding the Bitcoin digital currency system", Louisiana Law Review, vol. 73, No. 1, Summer 2013, pp. 1118-1153.

Meiklejohn, Sarah et al., "A fistful of bitcoins: Characterizing Payments among men with no names", 2013, (8 pages).

Wallace, Benjamin , "The rise and fall of bitcoin", Magazine, WIRED, https://www.wired.com/2011/11/mf_bitcoin/all/1/, Nov. 23, 2011, pp. 1-17.

"How to sell Lindens" dated Mar. 6, 2013 (Year: 2013).

"How Bitcoin Works, downloaded from <https://www.forbes.com/sites/investopedia/2013/08/01/how-bitcoin-works/#284bd94a17ff>, dated Aug. 1, 2013, attached as PDF file. (Year: 2013)".

"Strongcoin—The safest Bitcoin e-wallet on the planet", <https://www.javaworld.com/article/2078467/bitcoin-for-beginners-part-2--bitcoin-as-a-technology-and-network.html>, year 2013.

Neuman, Nick , "KeySplit—Tackling the hard parts of being your own bank", <https://medium.com/@nickneuman/keysplit-private-key-security-for-cryptocurrency-owners-d1653ea9631d>, Feb. 24, 2018.

Blockchain ("How do off chain transactions work?" downloaded from <https://bitcoin.stackexchange.com/questions/123530/how-do-off-chain-transactions-work>, year 2013.

"Send bitcoins to an unknown recipient", Feb. 13, 2011, downloaded from <https://bitcointalk.org/index.php?topic=3427.0>, (Year: 2011).

"Send Bitcoins to Email Addresses!", Jan. 9, 2012, downloaded from <https://web.archive.org/web/20120109084110/http://www.bitcoinmail.com/>, merged and attached as PDF file, (Year: 2012).

"You Can Now Send Bitcoins over Email with Tip Bot", Feb. 26, 2014, downloaded from <https://www.coindesk.com/can-now-send-bitcoins-email-tip-bot>, (Year: 2014).

International Search Report and Written Opinion for PCT Application No. PCT/US2019/027857 dated Jul. 15, 2019.

Quaddah et al. "FairAccess: a new Blockchain-based access control framework for the 1-20 Internet of Things." In: Security and Communication Networks. Feb. 19, 2017.

International Search Report and Written Opinion of the ISA dated Dec. 18, 2019 for PCT/US19/52371.

Bradbury, Danny , "BitGo Safe Aims to Secure Bitcoin Wallets with Multi-Signature Transactions", CoinDesk, The voice of Digital Currency, <http://web.archive.org/web/20140108021304/http://www.coindesk.com/>, published Dec. 19, 2013.

"Inputs.io FAQ", <https://inputs.io/faq>, 2013.

"Strongcoin—The safest Bitcoin e-wallet on the planet", <https://www.javaworld.com/article/2078467/bitcoin-for-beginners-part-2-bitcoin-as-a-technology-and-network.html>, year 2013.

Merkel, Dirk , "Bitcoin for beginners, Part 2: Bitcoin as a technology and network", Javaworld, Dec. 6, 2011.

"NPL4, Importing Bitcoin from a paper wallet into Electrum", <https://thecleverest.com/>, dated Mar. 12, 2014.

* cited by examiner




FIG. 1A




FIG. 1B

	First Host Computer System 14		
	Wallet A		
	Email address A; Login Details		
Transfer 1	Bitcoin address 1		
		From: First Host	
		Amount in bitcoin	
		Host Fee: x%	
Transfer 2	Bitcoin address 2		
		From: Network address	
		Amount in bitcoin	
		Host Fee: 0 bitcoin	

FIG. 2

	First Host Computer System 14			
	Wallet A		Wallet B	
	Email address A; Login Details		Email address B	
Transfer 1	Bitcoin address 1			
		From: First Host		
		Amount in bitcoin		
		Host Fee: x%		
Transfer 2	Bitcoin address 2			
		From: Network address		
		Amount in bitcoin		
		Host Fee: 0 bitcoin		
Transfer 3	Bitcoin address 2		Bitcoin address 3	
		To: Email address B		From: Wallet A
		Amount in bitcoin		Amount in bitcoin
		Miner's Fee = 0 bitcoin		
		Host Fee: 0 bitcoin		

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

←

→

https://coinbase.com/...

File

Edit

View

Favorites

Tools

Help

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

GENERAL

≡ Send/Request

⇌ Buy/Sell

⚙ Recurring Payments

⚙ Account Settings

MERCHANT TOOLS ▾

👤 Orders

👤 Subscribers

✖ Tools

⚙ Merchant Settings

Complete your profile

Next step: verify your phone

Get the Coinbase App

Use Coinbase easily on your Android phone.

+ Add a Bank Account

+ Add a Credit Card

+ Add a Billing Address

Bank Accounts

Used to buy and sell bitcoins – U.S. only

Enable Instant Buy

Credit Cards

Used as

Billing Addresses

Link A Bank Account

Type ☒ Checking ☐ Savings ☐ Business checking

Routing number 123456789

Account number 987654321

Your Full Name John B. Smith X

John Smith
100 Main Street
Anytown 10012
PAY TO THE
ORDER OF

102

MEMO

123456789 1002345678 102

Account No.

Routing No.
9 digits

Account No.

Cancel

Back

Next

ABOUT

About

Careers

Press

Legal

PRODUCT

How To Buy Bitcoin

Merchant Services

Developer Platform

Security

Support

© 2014 Coinbase

FIG. 9

https://coinbase.com/...			
File Edit View Favorites Tools Help		John.Smith@gmail.c... ▼	
0.00189 BTC ≈ 1.42 USD		Bank Accounts Used to buy and sell bitcoins – U.S. only Enable Instant Buy Regular buys take 4 business days – enable Instant Buy and get your coins in seconds. + Add a Bank Account	
GENERAL ≡ Send/Request ⇄ Buy/Sell ⚙ Recurring Payments ⚙ Account Settings MERCHANT TOOLS ▼ 👤 Orders 👤 Subscribers 🔧 Tools ⚙ Merchant Settings		Choose A Verification Method ☒ Instant Account Verification Takes a few minutes 1. Enter your online account credentials. 2. Coinbase will securely log in on your behalf and check your account information. 3. If the login is successful your account will be verified. ☐ Deposit Verification Takes 2-3 business days 1. We will make two small deposits to your account (and one debit for the combined amount). 2. You will see these credits in 2-3 days. 3. Enter the credit amounts and your account will be verified.	
Credit Card + Add a Credit Card Billing Address + Add a Billing Address		Cancel Back Next	
PRODUCT How To Buy Bitcoin Merchant Services Developer Platform Security		ABOUT About Careers Press Legal	
		Documentation Twitter Facebook © 2014 Coinbase	

FIG. 10

The screenshot displays the Coinbase website interface. At the top, the browser address bar shows 'https://coinbase.com/'. The navigation bar includes links for 'File', 'Edit', 'View', 'Favorites', 'Tools', and 'Help'. The main header area shows the current balance as '0.00189 BTC ≈ 1.42 USD' and the user's email 'John.Smith@gmail.c...'. The left sidebar contains a menu with 'GENERAL' (Send/Request, Buy/Sell, Recurring Payments, Account Settings), 'MERCHANT TOOLS' (Orders, Subscribers, Tools, Merchant Settings), 'Complete your profile' (Next step: verify your phone), and 'Get the Coinbase App' (Use Coinbase easily on your Android phone.). The main content area is titled 'Bank Accounts' and 'Used to buy and sell bitcoins – U.S. only'. It features a 'Bank Accounts' section with a '+ Add a Bank Account' button, a 'Credit' section with a '+ Add a' button, and a 'Billing' section with a '+ Add a B' button. The 'Instant Account Verification for Wells Fargo - Bank' section is highlighted, showing a 'Username' field and a 'Password' field. Below these fields, there is a message: 'Having trouble logging in? Visit your bank's website to check your credentials. This can take a few moments to process after clicking 'Next''. At the bottom of the verification section are 'Cancel', 'Back', and 'Next' buttons. The footer area includes links for 'PRODUCT' (How To Buy Bitcoin, Merchant Services, Developer Platform, Security), 'About' (Careers, Press, Legal), 'Documentation', 'Status', 'Support', and social media links for Twitter and Facebook, along with the copyright notice '© 2014 Coinbase'.

U.S. Patent

Aug. 25, 2020

Sheet 11 of 76

US 10,755,241 B2

FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

←

→

https://coinbase.com/...

🔍

▼

File

Edit

View

Favorites

Tools

Help

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

GENERAL

Send/Request

Buy/Sell

Recurring Payments

Account Settings

MERCHANT TOOLS ▼

Orders

Subscribers

Tools

Merchant Settings

Complete your profile

Next step: verify your phone

Get the Coinbase App

Use Coinbase easily on your Android phone.

PRODUCT

How To Buy Bitcoin

Merchant Services

Developer Platform

Security

Bank Accounts

Used to buy and sell bitcoins – U.S. only

+ Add a Bank Account

Enable Instant Buy

Regular buys take 4 business days – enable Instant Buy and get your coins in seconds

Credit Cards

+ Add a Credit Card

Billing Address

+ Add a Billing Address

Add a Credit Card

Name on card

Credit card number

Expires

CVC number

Billing address

Cancel

Add

© 2014 Coinbase

FIG. 16

[File](#)
[Edit](#)
[View](#)
[Favorites](#)
[Tools](#)
[Help](#)

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

GENERAL

- Send/Request
- Buy/Sell
- Recurring Payments
- Account Settings

MERCHANT TOOLS ▾

- Orders
- Subscribers
- Tools
- Merchant Settings

Complete your profile
 Next step: verify your phone

Get the Coinbase App
 Use Coinbase easily on your Android phone.

PRODUCT

- How To Buy Bitcoin
- Merchant Services
- Developer Platform
- Security

ABOUT

- About
- Careers
- Press
- Legal

Bank Accounts

Used to buy and sell bitcoins – U.S. only

Enable Instant Buy

+ Add a Bank Account

Credit Cards

+ Add a Credit Card

Billing Address

+ Add a Billing Address

Add a Billing Address

First name John
 Last name Smith
 Address 20011 City View Rd
 City Los Angeles
 State California
 ZIP Code 90001
 Billing address United States

Cancel

Add Address

Support © 2014 Coinbase

FIG. 17




FIG. 18




FIG. 19

←

→

https://coinbase.com/...

▼

🔍

📄

🏠

☆

⚙️

File Edit View Favorites Tools Help

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c... ▼

GENERAL

⚙️ Send/Request

🔄 Buy/Sell

💰 Recurring Payments

⚙️ Account Settings

MERCHANT TOOLS ▼

📄 Orders

👤 Subscribers

✖️ Tools

⚙️ Merchant Settings

Complete your profile

Next step: verify a credit card

Buy Bitcoin

Sell Bitcoin

History

Payment Methods

Limits and Verifications

🏠 Bank Accounts

+ Add a Bank Account

📇 Credit Cards

Visa credit *****3456

20011 City View

Verify

Remove

+ Add a Credit Card

📅 Billing Address

John Smith

20011 City View

Los Angeles, CA

US

Remove

+ Add a Billing Address

🔒 Complete Charge Verification

Used to buy and sell bitcoins – U.S. only

Those amounts didn't match our records

Please enter the two amounts (in cents) we charged to your credit card. This should appear soon or instantly under the **pending transactions** area of your credit card statement.

First Amount \$1. 36

Second Amount \$1. 27

For example, enter \$1.25 as "25". You can enter the amounts in either order. Help me identify verification charges on my credit card statement.

Cancel

Re-charge

Verify Charge Numbers

FIG. 20

←

→

https://coinbase.com/...

File

Edit

View

Favorites

Tools

Help

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

GENERAL

Send/Request

Buy/Sell

Recurring Payments

Account Settings

MERCHANT TOOLS

Orders

Subscribers

Tools

Merchant Settings

Complete your profile

Next step: verify a credit card

Buy Bitcoin

Sell Bitcoin

History

Payment Methods

Limits and Verifications

Bank Accounts

Used to buy and sell bitcoins – U.S. only

Wells Fargo - Bank *****5678

Remove

Primary

+ Add a Bank Account

Credit Cards

Used as backup payment method – Visa only

Visa credit *****3456

20011 City View

Verify

Remove

+ Add a Credit Card

Billing Address

John Smith

20011 City View

Los Angeles, CA

US

Remove

+ Add a Billing Address

Enable Instant Buy

Regular buys take 4 business days – enable Instant Buy and get your coins in seconds

1. Link a bank account

2. Add a Credit Card

3. Verify your identity

Credit Card Added

✓ Congratulations! Your card was added.

Enable Instant Buy

Regular purchases take 4 days – enable Instant Buy to get your coins in seconds.

Next step: Verify your identity >

Close

Verify your identity

FIG. 21

←

→

https://coinbase.com/...

File

Edit

View

Favorites

Tools

Help

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

GENERAL

Send/Request

Buy/Sell

Recurring Payments

Account Settings

MERCHANT TOOLS

Orders

Subscribers

Tools

Merchant Settings

Complete your profile

Next step: verify your phone

Account Settings

Referrals

Bitcoin Addresses

Integrations

Account Settings

Name

Email

Local currency

Time zone

Save Changes

Phone Numbers

+ Verify A Phone

Notifications

Email me when:

Save Changes

Reports

Export my

Change Password

Forgot Password?

Picture

Change Picture

United States, Dollar (USD)

(GMT -08:00) Pacific Time (US)

adding a phone enables two-factor authentication on your account. read more

transaction history

and email it to

Export

FIG. 22

←→

https://coinbase.com/...

File Edit View Favorites Tools Help

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

Account updated!

GENERAL

Send/Request

Buy/Sell

Recurring Payments

Account Settings

MERCHANT TOOLS

Orders

Subscribers

Tools

Merchant Settings

Complete your profile

Next step: verify your phone

Account Settings

Referrals

Bitcoin Addresses

Integrations

Account Settings

Name

John Smith

Email

John.Smith@gmail.com

Local currency

United States, Dollar (USD)

Time zone

(GMT -08:00) Pacific Time (US)

Save Changes

Password

Change Password

Forgot Password?

Change Picture

Phone Numbers

+ Verify A Phone

adding a phone enables two-factor authentication on your account. read more

Notifications

Email me when:

☒ I send or receive bitcoin

☒ I buy or sell bitcoin

☒ I receive merchant orders

☒ There are recommended actions for my account

Save Changes

Reports

Export my transaction history and email it to John.Smith@gmail.co...

Export

FIG. 23




FIG. 24

File Edit View Favorites Tools Help

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

Account updated!

GENERAL

- Send/Request
- Buy/Sell
- Recurring Payments
- Account Settings

MERCHANT TOOLS ▾

- Orders
- Subscribers
- Tools
- Merchant Settings

Complete your profile
Next step: verify your phone

Account Settings Referrals Bitcoin Addresses Integrations

Account Settings

Name John Smith Change Password
Email John.Smith@gmail.com Forgot Password?
Picture Change Picture

Verify A Phone Number

Choose a country United States
Your phone number +1 6508233835

Cancel Back Next

Reports

Export my transaction history and email it to John.Smith@gmail.co... Export

FIG. 25




FIG. 26

[File](#)
[Edit](#)
[View](#)
[Favorites](#)
[Tools](#)
[Help](#)

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

Account Settings

Account Settings

Referrals	Bitcoin Addresses	Integrations
Name John Smith	Password Change Password	Forgot Password?
Email John.Smith@gmail.com	Picture Change Picture	
Local currency United States, Dollar (USD)		
Time zone (GMT -08:00) Pacific Time (US)		
Save Changes		

Phone Numbers adding a phone enables two-factor authentication on your account. read more

+1 310 234 6789	VERIFIED	PRIMARY PHONE	Delete
-----------------	-----------------	----------------------	------------------------

You can also Google Authenticator and SMS access

Notifications

Email me when:

- ☒ I send or receive bitcoin
- ☒ I buy or sell bitcoin
- ☒ I receive merchant orders
- ☒ There are recommended actions for my account

[Save Changes](#)

Reports

Export my transaction history ☒ and email it to John.Smith@gmail.co... [Export](#)

GENERAL

- Send/Request
- Buy/Sell
- Recurring Payments
- Account Settings

MERCHANT TOOLS ▾

- Orders
- Subscribers
- Tools
- Merchant Settings

Complete your profile

Next step: verify your phone

FIG. 27

File Edit View Favorites Tools Help https://coinbase.com/... John.Smith@gmail.c... ▼																		
0.00189 BTC ≈ 1.42 USD																		
GENERAL - Send/Request - Buy/Sell - Recurring Payments - Account Settings MERCHANT TOOLS ▼ - Orders - Subscribers - Tools - Merchant Settings	ID Verification Confirm your identity to increase your buy/sell limits ID verification is an optional step for increasing your buy/sell limits. You can attempt once per 24 hours. Step 1: Basic Information <table border="1"> <tr> <td>First name</td> <td>John</td> </tr> <tr> <td>Last name</td> <td>Smith</td> </tr> <tr> <td>Address</td> <td>20011 City View Rd</td> </tr> <tr> <td>City</td> <td>Los Angeles</td> </tr> <tr> <td>State</td> <td>California ☒</td> </tr> <tr> <td>ZIP Code</td> <td>90001</td> </tr> <tr> <td>Last 4 Digits of SSN</td> <td>8099</td> </tr> <tr> <td>Date of Birth</td> <td>11 / 21 / 1964 ☒</td> </tr> </table> Next ➔		First name	John	Last name	Smith	Address	20011 City View Rd	City	Los Angeles	State	California ☒	ZIP Code	90001	Last 4 Digits of SSN	8099	Date of Birth	11 / 21 / 1964 ☒
First name	John																	
Last name	Smith																	
Address	20011 City View Rd																	
City	Los Angeles																	
State	California ☒																	
ZIP Code	90001																	
Last 4 Digits of SSN	8099																	
Date of Birth	11 / 21 / 1964 ☒																	
Complete your profile Next step: verify your identity																		
PRODUCT - How To Buy Bitcoin - Merchant Services - Developer Platform - Security	ABOUT - About - Careers - Press - Legal	RESOURCES - API - Documentation - Status - Support																
	FOLLOW US ON - Our Blog - Twitter - Facebook © 2014 Coinbase																	

FIG. 28

File Edit View Favorites Tools Help	
0.00189 BTC ≈ 1.42 USD	
John.Smith@gmail.c...	
GENERAL Send/Request Buy/Sell Recurring Payments Account Settings MERCHANT TOOLS ▾ Orders Subscribers Tools Merchant Settings	ID Verification Step 2: Questions Information pulled from public records Where was your social security number issued? ☐ Oregon ☒ California ☐ Arkansas ☐ None of the above ☐ Kentucky With which name are you associated? ☐ ARDONNE ☐ MARQUIS ☐ HANLEY ☒ None of the above ☐ ILFORD In which city is LEIGH AVE? ☐ BETHESDA ☐ SACRAMENTO ☐ HIGHLAND PARK ☐ None of the above ☒ LOS ANGELES How long have you been associated with the property at 20011 City View Rd? ☐ Less than 2 years ☒ 4 - 5 years ☐ 2 - 3 years ☐ Over 5 years ☐ 3 - 4 years ☐ None of the above Submit You have 4 minutes to complete
Complete your profile Next step: verify your identity	
PRODUCT How To Buy Bitcoin Merchant Services Developer Platform Security	

FIG. 29




FIG. 30

https://coinbase.com/...									
File Edit View Favorites Tools Help									
0.00189 BTC ≈ 1.42 USD John.Smith@gmail.c...									
GENERAL - Send/Request - Buy/Sell - Recurring Payments - Account Settings MERCHANT TOOLS - Orders - Subscribers - Tools - Merchant Settings Complete your profile Next step: verify a credit card	Account Settings Referrals Bitcoin Addresses Integrations For every friend you invite to Coinbase, we'll send both you and them \$5 worth of Bitcoin when they complete a buy or sell of at least \$100! Invite Friends Badges Invite your Gmail Contacts Send via email Share a link on social media. You choose which recipients on the next step. https://coinbase.com/?r=52b2 Copy URL Your referral link – you can paste this anywhere Users You've Referred <table border="1"> <tr> <td>Signed Up</td> <td>Referral Method</td> <td>Connected Bank Account</td> <td>Completed Buy/Sell</td> </tr> <tr> <td colspan="4">You haven't referred any users yet!</td> </tr> </table> Questions? Read more in our support center.	Signed Up	Referral Method	Connected Bank Account	Completed Buy/Sell	You haven't referred any users yet!			
Signed Up	Referral Method	Connected Bank Account	Completed Buy/Sell						
You haven't referred any users yet!									
PRODUCT - How To Buy Bitcoin - Merchant Services - Developer Platform - Security	ABOUT - About - Careers - Press - Legal RESOURCES - API - Documentation - Status - Support FOLLOW US ON - Our Blog - Twitter - Facebook © 2014 Coinbase								

FIG. 31

 									
https://coinbase.com/...									
File Edit View Favorites Tools Help									
0.00189 BTC ≈ 1.42 USD									
 John.Smith@gmail.c... ▼									
Account Settings Referrals Bitcoin Addresses Integrations									
GENERAL - Send/Request - Buy/Sell - Recurring Payments - Account Settings MERCHANT TOOLS ▼ - Orders - Subscribers - Tools - Merchant Settings									
My Bitcoin Addresses Your wallet on Coinbase is a collection of bitcoin addresses. New bitcoin addresses are automatically generated for each payment on Coinbase and stay associated with your account forever (so it is safe to reuse them). You can add a label or callback URL to an individual address by clicking 'Edit'. Callback urls can be used to receive automated notifications Search + Create New Address									
<table border="1"><thead><tr><th>Address</th><th>Label</th><th>Callback URL</th><th>Created</th></tr></thead><tbody><tr><td>1PqxXH7q7smsb57SA1QVF11BUMX1pXHAtw</td><td></td><td></td><td>15 days ago</td></tr></tbody></table>		Address	Label	Callback URL	Created	1PqxXH7q7smsb57SA1QVF11BUMX1pXHAtw			15 days ago
Address	Label	Callback URL	Created						
1PqxXH7q7smsb57SA1QVF11BUMX1pXHAtw			15 days ago						
Paper Wallets Export your bitcoins to private physical storage. Print A Paper Wallet Import A Paper Wallet									
PRODUCT - How To Buy Bitcoin - Merchant Services - Developer Platform - Security ABOUT - About - Careers - Press - Legal RESOURCES - API - Documentation - Status - Support FOLLOW US ON  Our Blog  Twitter  Facebook © 2014 Coinbase									

FIG. 32




FIG. 33

File Edit View Favorites Tools Help

0.00189 BTC ≈ 1.42 USD

John.Smith@gmail.c...

	Buy Bitcoin	Sell Bitcoin	History	Payment Methods	Limits and Verifications
GENERAL ≡ Send/Request ⇄ Buy/Sell ⚙ Recurring Payments ⚙ Account Settings MERCHANT TOOLS ▾ 👤 Orders 👤 Subscribers ⚙ Tools ⚙ Merchant Settings	You have 10.0 BTC remaining of your daily buy limit. View limits. BTC 1 X at \$757.43 USD each Enable ⚡ Instant Buy to get your coins in seconds instead of days. You can also set up a recurring buy.				
Complete your profile					
Next step: verify a credit card					
PRODUCT How To Buy Bitcoin Merchant Services Developer Platform Security	ABOUT About Careers Press Legal		RESOURCES API Documentation Status Support		
			FOLLOW US ON Our Blog Twitter Facebook © 2014 Coinbase		

FIG. 34

https://coinbase.com/... ▾ 🔍 📄 ✕

File Edit View Favorites Tools Help

0.00189 BTC ≈ 1.42 USD

GENERAL Send/Request Buy/Sell Recurring Payments Account Settings MERCHANT TOOLS ▾ Orders Subscribers Tools Merchant Settings	Buy Bitcoin Sell Bitcoin History Payment Methods Limits and Verifications Buy Amount BTC 1 ✕ at \$757.43 USD each You have 10.0 BTC remaining of your daily buy limit. View limits. Enable ⚡ Instant Buy to get your coins in seconds instead of days. Payment method Wells Fargo - Bank *****5678 ☒ Buy Confirmation X You are about to withdraw \$765.15 from your Wells Fargo - Bank *****5678. 1.00 BTC will arrive to your Coinbase account in 4 business days on Wednesday Jan 8, 2014. We will send you an email when your bitcoins arrive. Cancel Confirm
PRODUCT How To Buy Bitcoin Merchant Services Developer Platform Security	A A Careers Press Legal Documentation Status Support Twitter Facebook © 2014 Coinbase

FIG. 35




FIG. 36





FIG. 37



Hi John.Smith@gmail.com


On Jan 2, 2014 you purchased 1.00 BTC via bank transfer.

Those bitcoins are now available in your Coinbase account!

Thank you for the purchase.

Kind regards,
The Coinbase Team

FIG. 38



Hi John.Smith@gmail.com

Coinbase just sent you **0.00660667 BTC** (worth \$4.99 USD) using Coinbase.

Attached message:

Congrats! You just earned a referral bonus for completing your first bitcoin purchase/sale. Your friend RepresentativeA also got \$5.00 of bitcoin for telling you about Coinbase.

You and your friends will each receive \$5.00 of bitcoin when you refer them to Coinbase and they buy or sell their first bitcoin. Find out more on the <https://coinbase.com/account/referrals> page.

Click here to sign in and view this transaction

Kind regards,
The Coinbase Team

FIG. 39

←

→

https://coinbase.com/...

🔍

📄

✖

File

Edit

View

Favorites

Tools

Help

0.00189 BTC ≈ 1.42 USD

🌐 John.Smith@gmail.c...

🔧

GENERAL

⚙️ Send/Request

➡️ Buy/Sell

🔄 Recurring Payments

⚙️ Account Settings

MERCHANT TOOLS ▾

📄 Orders

👤 Subscribers

⚙️ Tools

⚙️ Merchant Settings

Complete your profile

Next step: verify a credit card

Buy Bitcoin

Sell Bitcoin

History

Payment Methods

Limits and Verifications

Limits and Verifications

Complete the verification steps below to raise your limits and enable instant buys.

Level	Daily Buy Limit	Weekly Instant Buy Limit	Daily Sell Limit
0	✓ \$0	✓ \$0	✓ \$0
1	\$3,000	\$3,000	\$3,000
2	\$50,000	\$50,000	\$50,000

Level 1

Verify Your Email Address
Click a link in the confirmation email

COMPLETE

Verify Your Phone
Enable two-factor authentication and increase your account security

COMPLETE

Add a Bank Account
Link and verify at least one bank account

COMPLETE

Level 2

Complete A Purchase
Buy some bitcoin and wait at least 30 days

PENDING

Verify Your Identity
Complete identity verification

Verify Now

Upload Identification
Verify a real-world ID document

Verify Now

Enable Instant Buy

Add a Credit Card
Link a backup payment method – Vasa only for now

Verify Now

FIG. 40

First Host Computer System 14				
Wallet A			Wallet B	
	Email Address A; Login Details		Email address B; Login Details	
Transfer 1	Bitcoin address 1			
		From: First Host		
		Amount in bitcoin		
		Host Fee: x%		
Transfer 2	Bitcoin address 2			
		From: Network address		
		Amount in bitcoin		
		Host Fee: 0 bitcoin		
Transfer 3	Bitcoin address 2		Bitcoin address 3	
		To: Email address B		From: Wallet A
		Amount in bitcoin		Amount in bitcoin
		Miner's Fee = 0 bitcoin		
		Host Fee: 0 bitcoin		
Transfer 4			Bitcoin address 4	
				From: First Host
				Amount in bitcoin
				Host Fee: x%
Transfer 5	Bitcoin address 5		Bitcoin address 4	
		From: Wallet B		To: Email address A
		Amount in bitcoin		Amount in bitcoin
				Miner's Fee = 0 bitcoin
				Host Fee: 0 bitcoin
Transfer 6	Bitcoin address 5		Bitcoin address 4	
		From: Wallet B		To: Bitcoin address 5
		Amount in bitcoin		Amount in bitcoin
				Miner's Fee = 0 bitcoin
				Host Fee: 0 bitcoin

FIG. 41

The screenshot displays the Coinbase web application interface. At the top, the browser address bar shows 'https://coinbase.com/'. The main navigation bar includes links for 'File', 'Edit', 'View', 'Favorites', 'Tools', and 'Help'. The user's profile is identified as 'John.Smith@gmail.c...'. The main content area is divided into several sections:

- GENERAL**: Includes links for 'Send/Request', 'Buy/Sell', 'Recurring Payments', and 'Account Settings'.
- MERCHANT TOOLS**: Includes links for 'Orders', 'Subscribers', 'Tools', and 'Merchant Settings'.
- Transactions**: Displays the 'Current Balance (hide)' as '0.00849667 BTC ≈ 6.45 USD'. It features buttons for 'Send Money' and 'Request Money'.
- Quickstart Guide**: A list of three steps: 1. Buy your first bitcoin by connecting a bank account. 2. Accept bitcoin payments on your website using our merchant tools. 3. Invite friends to give and get \$5 of bitcoin when they complete a buy.
- Send Money**: A modal window for sending funds. It includes a 'To:' field with the email 'representativea@coinbase.com', an 'Amount:' field with 'BTC .01' or 'USD 7.6', and a 'Message:' field with the text 'RepresentativeA, Here is the money that I owe you for the jacket, John B. Smith'. A progress bar indicates the transaction status, and a 'Next step: refer a friend' link is provided.

The 'Send Money' modal window also displays a table of transaction amounts:

Amount
+0.00660667
+1.00
+0.00189

FIG. 42




FIG. 43




FIG. 44

First Host Computer System 14				Second Host Computer System 16	
Wallet A		Wallet B		Wallet C	
	Email Address A: Login Details		Email Address B: Login Details		
Transfer 1	Bitcoin address 1				
	Amount in bitcoin				
	Bitcoin address 2				
Transfer 2		From: Network address			
		Amount in bitcoin			
		Host Fee: 0 bitcoin			
Transfer 3	Bitcoin address 2	Bitcoin address 3			
		To: Email address B	From: Wallet A		
		Amount in bitcoin	Amount in bitcoin		
		Miner's Fee = 0 bitcoin			
		Host Fee: 0 bitcoin			
Transfer 4		Bitcoin address 4			
			From: First Host		
			Amount in bitcoin		
			Host Fee: x%		
Transfer 5	Bitcoin address 5	Bitcoin address 4			
		From: Wallet B	To: Email address A		
		Amount in bitcoin	Amount in bitcoin		
			Miner's Fee = 0 bitcoin		
			Host Fee: 0 bitcoin		
Transfer 6	Bitcoin address 5	Bitcoin address 4			
		From: Wallet B	To: Email address A		
		Amount in bitcoin	Amount in bitcoin		
			Miner's Fee = 0 bitcoin		
			Host Fee: 0 bitcoin		
Transfer 7		Bitcoin address 4	Bitcoin address 6		
			To: Bitcoin Address 6	From: Wallet B (First Host)	
			Amount in bitcoin	Amount in bitcoin	
			Miner's Fee = 001 Bitcoin		
			Host Fee: 0 bitcoin		

FIG. 45




FIG. 46




FIG. 47




FIG. 48

Offline
Distribution
Module 72




FIG. 49








FIG. 50






FIG. 52




FIG. 53





FIG. 54

FIG. 55







FIG. 56

FIG. 57






FIG. 59




FIG. 58

The image shows a web browser window with a menu bar (File, Edit, View, Favorites, Tools, Help) and an address bar containing 'https://coinbase.com/...'. The main content area displays a 'Withdraw' dialog box. The dialog box has a title bar with a close button (X). It contains the following fields and controls:

- From:** My Vault 1 (50.00 BTC)
- To:** My Wallet (1.00 BTC)
- Amount:** BTC 10
- Message:** Withdrawing 10 BTC for investment purposes.
- Enter you 2-step verification code:** 0000000
- Buttons:** Cancel, Withdraw

FIG. 60




FIG. 61




FIG. 62






FIG. 63








FIG. 66




FIG. 67






FIG. 68








FIG. 71




FIG. 72




FIG. 73a




FIG. 73b




FIG. 73c




FIG. 73d




FIG. 73e




FIG. 73f




FIG. 74

HOT WALLET FOR HOLDING BITCOIN**CROSS-REFERENCE TO RELATED APPLICATIONS**

This patent application claims priority from U.S. Provisional Patent Application No. 61/954,434, filed on Mar. 17, 2014; U.S. Provisional Patent Application No. 61/990,017, filed on May 7, 2014; U.S. Provisional Patent Application No. 62/042,676, filed on Aug. 27, 2014; U.S. Provisional Patent Application No. 62/056,100, filed on Sep. 26, 2014; U.S. Provisional Patent Application No. 62/086,669, filed on Dec. 2, 2014 and U.S. Provisional Patent Application No. 62/099,992, filed on Jan. 5, 2015, each of which is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

1). Field of the Invention

This invention relates to a computer system and method for transacting bitcoin.

2). Discussion of Related Art

The Bitcoin network is a peer-to-peer payment system having a plurality of nodes that are connected to one another. Bitcoin exchange computer systems allow for users to exchange local currency into or out of bitcoin. Users send payments by broadcasting digitally signed messages to the Bitcoin network. Users may, for example, send and receive payments using mobile applications on mobile devices, client software or a web browser.

Transactions do not explicitly identify the payor and payee by name or wallet. Instead, a bitcoin transaction transfers ownership to a new address, referred to as a "Bitcoin address". The Bitcoin address is derived from the public portion of one or more cryptographic key pairs. The private portion of a key pair is not disclosed to the public. To send bitcoin sent to an address, a user broadcasts a payment message that is digitally signed with the associated private key.

Participants known as "miners" at miner computer systems verify and timestamp transactions into a shared public database called a "block chain". The miners are rewarded with transaction fees and newly minted bitcoin for their effort. The miner computer systems are specialized computers that append blocks of transactions to the block chain. Solving a cryptographic puzzle required to append a block carries a reward plus fees included in transactions in the block.

Host computer systems reside at various nodes and may host accounts or "wallets" that allow users to make and accept payments using bitcoin. The wallet stores the public key of the Bitcoin address and its associated private key.

The transfer of bitcoin may be an onerous task if the entire public key of the Bitcoin address has to be copied and transmitted.

When a transaction is made between two wallets at the same or different host computer systems, the transaction is broadcast to the Bitcoin network for block chain verification. Such a block chain verification may take a long time to complete. Miner fees are also associated with such a transfer and have to be paid by a host computer system requesting the transfer.

It may be a security concern for users that their Bitcoin addresses may be stolen from their wallets. Existing systems

do not provide a solution for maintaining security of Bitcoin addresses while still allowing the users to use Bitcoin addresses within their wallets for transacting with other users.

A merchant computer system often has an online store and a website. A customer at a customer computer system may use a browser to access the online store via the website. Items are displayed for purchase in a local currency. Exchange rate between bitcoin and local currency changes over short periods of time. The price in local currency may thus change between the time that the local currency is displayed to the customer and the time that the customer decides to make the purchase. As a result, the customer or the merchant may incur a loss in local currency. The customer or merchant may then be reluctant to purchase using bitcoin.

In order for a user to access their wallet, the user may log into their account through the website using a user name and password. If the user name and password become compromised then it may be possible for bitcoin to be stolen out of the wallet. Users may therefore be reluctant to store bitcoin in their wallets without any additional security features.

Bitcoin transacting requires the use of a public key and a private key. The private key is used to sign an authorization and the public key is used to verify the signature. Some users may require control over their private keys in order to ensure to such users that bitcoin transacting will not take place without their express authorization.

Content creators often put a lot of time and energy into their blog posts. These efforts are rarely rewarded because efficient technology does not exist for rewarding bloggers for their efforts.

SUMMARY OF THE INVENTION

The invention provides a host computer system for transacting bitcoin including a processor, a network interface device connected to the processor, a computer readable medium connected to the processor, a data store on the computer readable medium and a set of instructions on the computer readable medium that are executable by the processor. The set of instructions includes a wallet establishment module, a login module, a hosted email module and a wallet management. The wallet establishment module establishes a first wallet in the data store, stores login details for the first wallet and storing a value representative of an amount of bitcoin held by the first wallet. The login module receives login credentials over the network interface device for the first wallet from a first user device, verifies whether the login credentials match the login details for the first wallet, and if the login credentials match the login details then logs the first user device into the first wallet. The hosted email module, if the first user device is logged into the wallet, permits transmission of an email by a user of the first user device to an email address of a second user device. The wallet management module, in response to the transmission of the email, records a transfer in the first wallet for an amount of bitcoin from the first wallet to a second wallet identified by the email address.

The invention also provides a method of transacting bitcoin. A processor establishes a first wallet in a data store connected to the processor. The processor stores login details for the first wallet. The processor stores a value representative of an amount of bitcoin held by the first wallet. The processor receives login credentials for the first wallet from a first user device. The processor verifies whether the login credentials match the login details for the

first wallet. The processor, if the login credentials match the login details then, logs the first user device into the first wallet. The processor, if the first user device is logged into the wallet, permits transmission of an email by a user to the first user device to an email address of a second user device and in response to the transmission of the email. The processor records a transfer in the first wallet for an amount of bitcoin from the first wallet to a second wallet identified by the email address.

The invention further provides a non-transitory computer-readable medium having stored thereon a set of instructions that are executable by a processor to carry out a method of transacting bitcoin. The processor establishes a first wallet in a data store connected to the processor. The processor stores login details for the first wallet. The processor stores a value representative of an amount of bitcoin held by the first wallet. The processor receives login credentials for the first wallet from a first user device. The processor verifies whether the login credentials match the login details for the first wallet. The processor, if the login credentials match the login details then, logs the first user device into the first wallet. The processor, if the first user device is logged into the wallet, permits transmission of an email by a user to the first user device to an email address of a second user device and in response to the transmission of the email. The processor records a transfer in the first wallet for an amount of bitcoin from the first wallet to a second wallet identified by the email address.

The invention further provides a first host computer system for transacting bitcoin including a processor at a first node of the Bitcoin network, a network interface device connected to the processor, a computer readable medium connected to the processor, a data store on the computer readable medium and a set of instructions on the computer readable medium that are executable by the processor. The set of instructions includes a wallet establishment module. The wallet establishment module establishes a first and second wallets in the data store and stores a value representative of an amount of bitcoin held by the first wallet. The wallet management module receives, over the network interface device, a first transfer instruction for an amount of bitcoin from the first wallet and an identifier of the second wallet, in response to the first transfer instruction, records a transfer in the first wallet for the amount of bitcoin in the first transfer instruction out of the first wallet and a transfer in the second wallet, identified by the identifier of the second wallet, for the amount of bitcoin in the first transfer instruction into the second wallet without paying a miner's fee for the first transfer. In order to execute a subsequent on-block chain transaction, the wallet management module receives, over the network interface device, a second transfer instruction for an amount of bitcoin from the first wallet and a bitcoin address associated with a second node of the Bitcoin network, and in response to the second transfer instruction, records a transfer in the first wallet for the amount of bitcoin in the second transfer instruction out of the first wallet, broadcasts a message to the Bitcoin network, including to the second node, to record a transfer associated with the bitcoin address associated with the second node, for the amount of bitcoin in the second transfer instruction, and pays a miner's fee for the second transfer.

The invention further provides a method of transacting bitcoin including. A processor of a first host computer system at a first node of the Bitcoin network establishes first and second wallets in a data store connected to the processor. The processor stores a value representative of an amount of bitcoin held by the first wallet. The processor receives a first

transfer instruction for an amount of bitcoin from the first wallet and an identifier of the second wallet. The processor, in response to the first transfer instruction, records a transfer in the first wallet for the amount of bitcoin in the first transfer instruction out of the first wallet and a transfer in the second wallet, identified by the identifier of the second wallet, for the amount of bitcoin in the first transfer instruction into the second wallet without paying a miner's fee for the first transfer. The processor receives a second transfer instruction for an amount of bitcoin from the first wallet and a bitcoin address associated with a second node of the bitcoin network. The processor, in response to the second transfer instruction records a transfer in the first wallet for the amount of bitcoin in the second transfer instruction out of the first wallet, broadcasts a message to the Bitcoin network, including to the second node, to record a transfer associated with the bitcoin address associated with the second node, for the amount of bitcoin in the second transfer instruction and pays a miner's fee for the second transfer.

The invention further provides a non-transitory computer-readable medium having stored thereon a set of instructions that are executable by a processor of a first host computer system at a first node of the Bitcoin network to carry out a method of transacting bitcoin. The processor establishes first and second wallets in a data store connected to the processor. The processor stores a value representative of an amount of bitcoin held by the first wallet. The processor receives a first transfer instruction for an amount of bitcoin from the first wallet and an identifier of the second wallet. The processor, in response to the first transfer instruction, records a transfer in the first wallet for the amount of bitcoin in the first transfer instruction out of the first wallet and a transfer in the second wallet, identified by the identifier of the second wallet, for the amount of bitcoin in the first transfer instruction into the second wallet without paying a miner's fee for the first transfer. The processor receives a second transfer instruction for an amount of bitcoin from the first wallet and a bitcoin address associated with a second node of the bitcoin network. The processor, in response to the second transfer instruction records a transfer in the first wallet for the amount of bitcoin in the second transfer instruction out of the first wallet, broadcasts a message to the Bitcoin network, including to the second node, to record a transfer associated with the bitcoin address associated with the second node, for the amount of bitcoin in the second transfer instruction and pays a miner's fee for the second transfer.

The invention also provides a host computer system for transacting bitcoin including a processor, a computer readable medium connected to the processor, a local storage on the computer readable medium and a set of instructions on the computer readable medium that are executable by the processor. The set of instructions includes a register, a Bitcoin address and an associated private key and value stored in the register, a local controller, a splitter, an offline distribution module, at least one restoration interface, and an assembler. The local controller transfers a private key for a Bitcoin address of a vault, to a local storage connected to a processor and transfers the value of the Bitcoin address in the register to the vault. The splitter splits the private key of the Bitcoin address of the vault into a plurality of codes. The offline distribution module distributes the codes to remote distributed storage locations, removes the private key of the Bitcoin address of the vault from the local storage, and removes the value for the Bitcoin address of the register from the Bitcoin address of the register. The restoration interface receives at least some of the codes into which the private key for Bitcoin address of the vault has been split.

5

The assembler assembles the codes that have been received into the private key of the Bitcoin address of the vault. The local controller restores the private key of the Bitcoin address of the vault from the local storage, and restores the value for the Bitcoin address in the register from the vault.

The invention further provides a method of transacting bitcoin. A processor transfers a private key of the Bitcoin address of a vault to a local storage connected to the processor. The processor splits the private key of the Bitcoin address of the vault into a plurality of codes. The processor distributes the codes to remote distributed storage locations. The processor transfers a value of a Bitcoin address in a register to the vault. The processor receives at least some of the codes into which the private key of the Bitcoin address of the vault has been split. The processor assembles the codes that have been received into the private key of the Bitcoin address of the vault. The processor restores the private key of the Bitcoin address of the vault to the vault. The processor restores the value of the Bitcoin address in the register from the vault.

The invention also provides a non-transitory computer-readable medium having stored thereon a set of instructions that are executable by a processor to carry out a method of transacting bitcoin. A processor transfers a private key of the Bitcoin address of a vault to a local storage connected to the processor. The processor splits the private key of the Bitcoin address of the vault into a plurality of codes. The processor distributes the codes to remote distributed storage locations. The processor transfers a value of a Bitcoin address in a register to the vault. The processor receives at least some of the codes into which the private key of the Bitcoin address of the vault has been split. The processor assembles the codes that have been received into the private key of the Bitcoin address of the vault. The processor restores the private key of the Bitcoin address of the vault to the vault. The processor restores the value of the Bitcoin address in the register from the vault.

The invention further provides a host computer system for transacting bitcoin including a processor, a network interface device connected to the processor, a computer readable medium connected to the processor, a local storage on the computer readable medium and a set of instructions on the computer readable medium that are executable by the processor. The set of instructions includes a wallet, a plurality of Bitcoin addresses stored in the wallet, a first vault, and a local controller. The local controller is executable for selecting a first transfer set of the Bitcoin addresses for cold storage in the first vault, transferring at least a portion of each of the Bitcoin addresses of the first transfer set to a first vault while keeping the portions a first transaction set in the register, and restoring at least the portion of the Bitcoin addresses of the first transfer set from the first vault to the wallet and a wallet management module transacting using the Bitcoin addresses of the first transacting set without permitting transacting with the Bitcoin addresses of the first transfer set due to the portions thereof being restored to the first vault, and transacting using the Bitcoin addresses of the first transfer set due to the portions thereof being restored from the first vault to the wallet.

The invention also provides a method of transacting bitcoin. A processor stores a plurality of Bitcoin addresses in a wallet. The processor selects a first transfer set of the Bitcoin addresses for cold storage in a first vault. The processor transfers at least a portion of each of the Bitcoin addresses of the first transfer set to the first vault while keeping the portions a first transaction set in the register. The processor transacts using the Bitcoin addresses of the first

6

transacting set without permitting transacting with the Bitcoin addresses of the first transfer set due to the portions thereof being transferred to the first vault. The processor restores the portion of the Bitcoin addresses of the first transfer set from the first vault to the wallet. The processor transacts using the Bitcoin addresses of the first transfer set due to the portions thereof being restored from the first vault to the wallet.

The invention further provides a non-transitory computer-readable medium having stored thereon a set of instructions that are executable by a processor to carry out a method of transacting. A processor stores a plurality of Bitcoin addresses in a wallet. The processor selects a first transfer set of the Bitcoin addresses for cold storage in a first vault. The processor transfers at least a portion of each of the Bitcoin addresses of the first transfer set to the first vault while keeping the portions a first transaction set in the register. The processor transacts using the Bitcoin addresses of the first transacting set without permitting transacting with the Bitcoin addresses of the first transfer set due to the portions thereof being transferred to the first vault. The processor restores the portion of the Bitcoin addresses of the first transfer set from the first vault to the wallet. The processor transacts using the Bitcoin addresses of the first transfer set due to the portions thereof being restored from the first vault to the wallet.

The invention also provides a method of effecting payment including receiving, by a host computer system, a request for payment from a merchant computer system, including an amount in a currency, determining, by the host computer system, a first exchange rate, wherein the first exchange rate fluctuates and the first exchange rate is determined at a first moment in time, converting, by the host computer system, the amount in the currency to an amount in bitcoin using the first exchange rate at the first moment in time, receiving, by the host computer system, a send instruction from the customer computer system, wherein the send instruction is at a second moment in time later than the first moment in time and the exchange rate at the second moment in time is a second exchange rate that is different than the first exchange rate at the first moment in time, receiving, by the host computer system, payment in bitcoin from the customer in an amount that is based on the amount in bitcoin and transmitting, by the host computer system, in response to receiving the send instruction from the customer computer system, a payment instruction to pay currency to the merchant, wherein the currency paid to the merchant is for an amount that is at least in part based on the amount in the currency that is converted to bitcoin at the first moment in time even though the exchange rate is different at the second moment in time.

The invention further provides a host computer system for effecting payment including a processor, a computer readable medium connected to the processor and a set of instructions on the computer readable medium that are executable by the processor. The set of instructions includes an application programmable interface (API) receiving a request for payment from a merchant computer system, including an amount in a currency, a currency converter determining a first exchange rate, wherein the first exchange rate fluctuates and the first exchange rate is determined at a first moment in time, and converting, by the host computer system, the amount in the currency to an amount in bitcoin using the first exchange rate at the first moment in time, transaction processor receiving a send instruction from the customer computer system, wherein the send instruction is at a second moment in time later than the first moment in

time and the exchange rate at the second moment in time is a second exchange rate that is different than the first exchange rate at the first moment in time, and receiving a payment in bitcoin from the customer in an amount that is based on the amount in bitcoin and a bank transfer module transmitting in response to receiving the send instruction from the customer computer system, a payment instruction to pay currency to the merchant, wherein the currency paid to the merchant is for an amount that is at least in part based on the amount in the currency that is converted to bitcoin at the first moment in time even though the exchange rate is different at the second moment in time.

The invention also provides a non-transitory computer-readable medium having stored thereon a set of instructions that are executable by a processor to carry out a method of transacting bitcoin including receiving, by a host computer system, a request for payment from a merchant computer system, including an amount in a currency, determining, by the host computer system, a first exchange rate, wherein the first exchange rate fluctuates and the first exchange rate is determined at a first moment in time, converting, by the host computer system, the amount in the currency to an amount in bitcoin using the first exchange rate at the first moment in time, receiving, by the host computer system, a send instruction from the customer computer system, wherein the send instruction is at a second moment in time later than the first moment in time and the exchange rate at the second moment in time is a second exchange rate that is different than the first exchange rate at the first moment in time, receiving, by the host computer system, payment in bitcoin from the customer in an amount that is based on the amount in bitcoin and transmitting, by the host computer system, in response to receiving the send instruction from the customer computer system, a payment instruction to pay currency to the merchant, wherein the currency paid to the merchant is for an amount that is at least in part based on the amount in the currency that is converted to bitcoin at the first moment in time even though the exchange rate is different at the second moment in time.

The invention further provides a method of managing bitcoin, including establishing, by a host computer system, a vault and storing first and second electronic communication addresses in relation to the vault, storing, by the host computer system, bitcoin in the vault, receiving, by the host computer system, a request to transfer an amount of the bitcoin out of the vault, transmitting, by the host computer system, in response to the request, first and second messages over a network to the first and second addresses, detecting, by the host computer system, whether first and second authorization instructions are received due to one or more users reacting to the first and second messages sent to the first and second addresses and transferring, by the host computer system, the amount of bitcoin out of the vault only if both the first and second authorization instructions are detected.

The invention also provides a non-transitory computer-readable medium having stored thereon a set of instructions which, when executed by a processor, executes a method including establishing, by a host computer system, a vault and storing first and second electronic communication addresses in relation to the vault, storing, by the host computer system, bitcoin in the vault, receiving, by the host computer system, a request to transfer an amount of the bitcoin out of the vault, transmitting, by the host computer system, in response to the request, first and second messages over a network to the first and second addresses, detecting, by the host computer system, whether first and second

authorization instructions are received due to one or more users reacting to the first and second messages sent to the first and second addresses and transferring, by the host computer system, the amount of bitcoin out of the vault only if both the first and second authorization instructions are detected.

The invention further provides a bitcoin management system, including a processor, a computer-readable medium connected to the processor and a set of instructions on the computer readable medium that are executable by the processor. The set of instructions includes a vault establishment wizard establishing a vault and storing first and second electronic communication addresses in relation to the vault, transaction processor storing bitcoin in the vault and a vault management module receiving a request to transfer an amount of the bitcoin out of the vault, transmitting, in response to the request, first and second messages over a network to the first and second addresses, detecting whether first and second authorization instructions are received due to one or more users reacting to the first and second messages sent to the first and second addresses, and instructing the transaction processor to transfer the amount of bitcoin out of the vault only if both the first and second authorization instructions are detected.

The invention also provides a method of transacting bitcoin including storing, by a host computer system, a public key, receiving, by the host computer system, a request from a user computer system to transact using a bitcoin address, transmitting, by the host computer system, a verification script to the user computer system, the verification script including an authorization and a signature algorithm that is executable on the user computer system to sign the authorization with a private key to obtain a signed authorization that includes the signature and transmit the signed authorization to the host computer system, receiving, by the host computer system, the signed authorization including the signature from the user computer system, verifying, by the host computer system, the signature of the signed authorization received from the user computer system using a public key; and transacting, by the host computer system, with the bitcoin address, the transacting being permitted due to a successful verification of the signature but not upon an unsuccessful verification of the signature.

The invention further provides a host computer system including a processor, a set of data and instructions on the computer-readable medium that are executable by the processor that are executable by the processor, a public key, a transaction processor receiving a request from a user computer system to transact using a bitcoin address, a verification script that is transmitted to the user computer system, the verification script including an authorization and a signature algorithm that is executable on the user computer system to sign the authorization with a private key to obtain a signed authorization that includes the signature and transmit the signed authorization to the host computer system, the host computer system receiving the signed authorization including the signature from the user computer system, and a verification module verifying the signature of the signed authorization received from the user computer system using a public key, the transaction processor transacting with the bitcoin address, the transacting being permitted due to a successful verification of the signature but not upon an unsuccessful verification of the signature.

The invention also provides a host computer system including a processor, a network interface device connected to the processor, a computer readable medium connected to the processor and a set of instructions on the computer

readable medium that are readable and executable by the processor. The set of instructions include an embedded code generator generating an embedded code for inclusion within a website of a partner computer system, the embedded code including a startup caller causing transmission of a startup call from the sender computer system to the host computer system, a startup call responder receiving the startup call from the sender computer system and transmitting, in response to the startup call, a tip button and a session script to the sender computer system, the session script being executable by the sender computer system to transmit a session call to the host computer system and a session responder transmitting, in response to the session call, at least one payment button and a payment script to the sender computer system, the payment button being selectable by the user of the sender computer system to execute the payment script, the payment script transmitting an instruction to a transaction processor to transfer funds from a sender account to a receiver account.

The invention further provides a method of transferring funds including generating, by a host computer system, an embedded code for inclusion within a website of a partner computer system, the embedded code including a startup caller causing transmission of a startup call from the sender computer system to the host computer system, receiving, by the host computer system, the startup call from the sender computer system, transmitting, by the host computer system in response to the startup call, a tip button and a session script to the sender computer system, the session script being executable by the sender computer system to transmit a session call to the host computer system and transmitting, by the host computer system in response to the session call, at least one payment selection and a payment script to the sender computer system, the payment selection being selectable by the user of the sender computer system to execute the payment script, the payment script transmitting an instruction to a transaction processor to transfer funds from a sender account to a receiver account.

The invention also provides a method of transacting bitcoin including executing, by a host computer system, a trading algorithm, including receiving sell offers for bitcoin from a sellers, receiving a buy offers for bitcoin from a buyers, creating respective matches wherein each match includes one of the buy offers and one of the sell offers, broadcasting each respective match over a multicast pipeline, receiving each respective match with a clearing module and clearing the respective match by updating an exchange database to reflect the respective match by transferring a representation of bitcoin from the seller to the buyer and transferring a representation of currency from the buyer to the seller.

The invention further provides a system for transacting bitcoin including an order gateway receiving sell offers for bitcoin from a sellers and receiving a buy offers for bitcoin from a buyers, a matching engine creating respective matches wherein each match includes one of the buy offers and one of the sell offers, a multicast pipeline, the matching engine broadcasting each respective match over the multicast pipeline, an exchange database; and a clearing module receiving each respective and clearing the respective match by updating the exchange database to reflect the respective match by transferring a representation of bitcoin from the seller to the buyer and transferring a representation of currency from the buyer to the seller, thereby executing a trading algorithm.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is further described by way of example with reference to the accompanying drawings, wherein:

FIG. 1A is a block diagram of a network environment that includes the Bitcoin network and a number of systems forming part thereof or connected thereto;

FIG. 1B is a block diagram of a first host computer system and a first and second user devices connected thereto;

FIG. 2 is diagrammatic view of a first wallet that is held within a first host computer system in FIG. 1;

FIG. 3 is a view similar to FIG. 2, further illustrating a second wallet that has been established within the first host computer system;

FIG. 4 is a view of an email that is received by the second user device in FIG. 1;

FIG. 5 is a view of a browser displaying a user interface with fields for creating login details for the second wallet;

FIGS. 6 to 30 are views similar to FIG. 5 that step a user of the second user device through a wallet set up;

FIGS. 31 to 33 are views of the browser wherein the user interface discloses various tools that can be used by the user;

FIGS. 34 to 37 are views of the browser wherein the user interface is used by the user to purchase bitcoin from the first host computer system;

FIG. 38 is an email that is received by the second user device to confirm the purchase of the bitcoin from the first host computer system;

FIG. 39 is an email that is received by the second user device with a notification that bitcoin has been added to their wallet as part of a referral bonus system;

FIG. 40 is a view of the browser wherein the user interface displays "Limits and Verifications" associated with the second wallet;

FIG. 41 is a view similar to FIG. 3 displaying transfer of bitcoin from the second wallet to the first wallet;

FIGS. 42 and 43 are views of the browser when the user interface steps the user through the transfer of bitcoin from the second wallet to the first wallet;

FIG. 44 is a view of the browser wherein the user interface displays Bitcoin addresses associated with transactions that have been completed;

FIG. 45 is a view similar to FIG. 40 further showing the transfer of bitcoin from the second wallet to a third wallet that is connected to a second host computer system;

FIG. 46 is a block diagram illustrating splitting of a private key of a vault and offline distribution;

FIG. 47 is a block diagram illustrating removal of the private key of the vault;

FIG. 48 is a block diagram illustrating offline or "cold" storage of values of Bitcoin addresses of a wallet in the vault;

FIG. 49 is a block diagram illustrating isolation of the vault with its private key removed;

FIG. 50 is a block diagram illustrating how the private key of the vault and the value of the Bitcoin addresses are restored;

FIGS. 51a to 51d are block diagrams that illustrate how values of certain Bitcoin addresses in a wallet are removed and others are maintained;

FIG. 52 is a graph illustrating how the wallet is maintained within a range so that only a portion of the wallet is "hot" in the sense that a user of the wallet can use the "hot" portion for transacting with another user;

FIG. 53 is a block diagram that shows how an intermediate hot wallet is used to collect value from multiple wallets before transfer to a vault;

FIG. 54 is a block diagram of a network environment that includes a customer computer system and merchant computer system;

11

FIG. 55 is a block diagram illustrating functioning for purposes of locking an exchange rate in when processing a transaction made by the customer computer system on the merchant computer system in FIG. 54;

FIG. 56 is a flow chart illustrating the establishment of a personal vault;

FIG. 57 is a flow chart illustrating how bitcoin is transferred into and out of the vault;

FIG. 58 is a block diagram of the first host computer system illustrating components that are used for establishing the vault and transferring bitcoin into and out of the vault;

FIG. 59 is an email that is transmitted to verify a secondary email address;

FIG. 60 is a view of a browser wherein a user interface displays options for transferring bitcoin out of a vault;

FIGS. 61 and 62 are emails that are transmitted to primary and secondary email addresses to approve a withdrawal;

FIG. 63 is a view of the browser with the user interface displaying a transaction status window;

FIG. 64 is a block diagram illustrating the establishment of a user-controlled vault;

FIG. 65 is a block diagram illustrating the user of the user-controlled vault for authorizing a transaction;

FIG. 66 is a block diagram of an address generator that is used by the user-controlled vault;

FIG. 67 to FIG. 71 are a block diagrams illustrating the functioning of a tip button;

FIG. 72 is a block diagram of a system for transacting bitcoin according to an embodiment of the invention;

FIGS. 73a to 73f illustrate the use of the system of FIG. 72 for executing transfer-in, trading and withdrawal algorithms; and

FIG. 74 is a block diagram of a machine in the form of a computer system forming part of the network environment.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1A of the accompanying drawings illustrates a network environment 10, including the Bitcoin network 12, a first host computer system 14 within which the invention manifests itself, a second host computer system 16, first and second user devices 18 and 20 connected over the Internet 22 to the first host computer system 14, a third user device 24 connected to the second host computer system 16, a bitcoin exchange computer system 26 and a miner computer system 28.

The Bitcoin network 12 includes a host node 30 and a plurality of remote nodes 32A to D that are connected to one another. The first host computer system 14 is connected to the host node 30. The bitcoin exchange computer system 26 is connected to the remote node 32A. The second host computer system 16 is connected to the remote node 32B. The miner computer system 28 is connected to the remote node 32D or could reside on the same computer system.

The first host computer system 14 is used primarily for transacting bitcoin and, as shown in FIG. 1B, includes a website 34 having a user interface 36, a login module 38, a wallet establishment module 40, a plurality of wallets 42, a wallet management module 44 and a hosted email module 46. The login module 38 is connected to the website 34 and the hosted email module 46 is connected to the login module 38. The wallet establishment module 40 is connected to the wallets 42. The hosted email module 46 is connected via the wallet management module 44 to the wallets 42. As illustrated in the drawing, the first user device 18 is connected over the Internet 22 and the user interface 36 to the login

12

module 38. As further illustrated in the drawing, the hosted email module 46 is connected over the Internet 22 to the second user device 20 and the second user device 20 is connected over the Internet 22 and the user interface 36 to the wallet establishment module 40.

As shown in FIG. 2, the first host computer system 14 already has one wallet (Wallet A) stored among the wallets 42 corresponding to the first user device 18. The first wallet (Wallet A) includes an email address (email address A) and login details for the wallet. The first wallet (Wallet A) also includes a number of Bitcoin addresses (Bitcoin address 1; Bitcoin address 2) that have been created due to respective transfers or purchases (Transfer 1; Transfer 2). The first Bitcoin address (Bitcoin address 1) is created due to a purchase (Transfer 1) from a master wallet of the first host computer system 14 (First Host) and is recorded for a value in an amount in bitcoin. The second Bitcoin address (Bitcoin address 2) is created due to a transfer (Transfer 2) from another location within the Bitcoin network 12 having a network address outside of the first host computer system 14 and is recorded for a particular amount in bitcoin. The first wallet (Wallet A) was originally established by the wallet establishment module 40 in FIG. 1B. The email address (email address A) and login details of the first wallet were also recorded by the wallet establishment module 40. The wallet establishment module 40 and wallet management module 44 were used to record the transfers and purchases (Transfer 1; Transfer 2), their Bitcoin addresses (Bitcoin address 1; Bitcoin address 2), their values and other details within the wallet.

A user of the first user device 18 in FIG. 1B may use a mobile application on the first user device 18 to communicate over the Internet 22 directly with the login module 38 or may use a browser on the first user device 18 to communicate via the Internet 22 and the website 34 with the login module 38. A browser application on the first user device 18 transmits a user interface request over the Internet 22 to the website 34. The website 34 responds to the user interface request by transmitting the user interface 36 over the Internet 22 to the first user device 18. The user interface 36 is then displayed on the first user device 18. The user interface 36 includes fields for entering login credentials, which are then transmitted from the first user device 18 over the Internet 22 to the login module 38. The login module 38 verifies whether the login credentials match the login details for the wallet (Wallet A). If the login credentials match the login details, then the login module 38 logs the first user device 18 into the wallet (Wallet A) in FIG. 2. If the login credentials do not match the login details, then the first user device 18 is not logged in to the wallet.

If the first user device 18 in FIG. 1B is logged in to the wallet, the login module 38 also provides access for the first user device 18 to the hosted email module 46 and transmission of an email by a user of the first user device 18 to an email address of the second user device 20. The user interface 36 provides a field for entering the email address of the second user device 20. The user interface 36 also includes a field for entering an amount in bitcoin (or an amount in local currency that is converted to bitcoin using an exchange rate) that is being transferred from the wallet (Wallet A) corresponding to the first user device 18 to a respective wallet among the wallets 42 corresponding to the second user device 20 that has not yet been established at this point in time. The user of the first user device 18 then uses the hosted email module 46 to send an email at 50 to the second user device 20. The hosted email module 46 simultaneously at 52 instructs the wallet establishment mod-

13

ule 40 to establish a wallet corresponding to the email address within the wallets 42. The hosted email module 46 simultaneously instructs the wallet management module 44 to record the amount of bitcoin that is being transferred from the wallet (Wallet A) within the wallet corresponding to the email address.

FIG. 3 illustrates further activity within the wallets 42 due to the email represented by a third transfer (Transfer 3). When the user of the first wallet (Wallet A) transmits the email, the system uses an existing Bitcoin address (Bitcoin address 2) to which the outgoing transfer is charged. Associated with the transfer (Transfer 3) are the email address to which the email has been transmitted, the amount in bitcoin, a miner's fee of zero bitcoin that is paid by the first host computer system 14 to any miner computer system such as the miner computer system 28 in FIG. 1A, and a host fee of zero bitcoin that are charged to the wallet (Wallet A) for the transfer. A second wallet (Wallet B) is established by the wallet establishment module 40 and the email address (email address B) of the second user device 20 is recorded as an identifier of the wallet (Wallet B). A Bitcoin address (Bitcoin address 3) is recorded within the second wallet (Wallet B) for the transfer (Transfer 3). Within the second wallet (Wallet B), the transfer (Transfer 3) has the Bitcoin address (Bitcoin address 3), the identifier of the wallet (Wallet A) from where the funds are transferred associated therewith, and the amount in bitcoin that has been transferred. The amount in bitcoin corresponding to the transfer (Transfer 3) of both wallets (Wallet A; Wallet B) is the same, consistent with double entry accounting principles. The second wallet (Wallet B) so far has no login details or any other user information and has not been accessed by a user of the second user device 20 at this point in time.

FIG. 4 illustrates the email when it is received at the second user device 20 in FIG. 1B. The email is received and viewed within an email application on the second user device 20. The email includes a link ("Click here to sign in and claim this amount") that, when selected by the user of the second user device 20, transmits a user interface request from the browser on the second user device 20 over the Internet 22 to the website 34. The website 34 responds to the user interface request to transmit the user interface 36 over the Internet 22 to the second user device 20 for viewing within the browser.

FIG. 5 illustrates the user interface 36 as displayed on the second user device 20 in FIG. 1B. The user interface 36 includes a plurality of fields for the user of the second user device 20 to enter login details for the second wallet (Wallet B), including a password and a confirmation of the password. After the user has entered a password, the user can access their wallet by selecting the button "Access My Wallet". The wallet establishment module 40 in FIG. 1B stores the login credentials in association with the second wallet (Wallet B). The login module 38 also logs the second user device 20 into the second wallet (Wallet B). If the user is logged out, the user can be provided with a login page where the user can enter login credentials that are compared with the login details in the second wallet (Wallet B) and then log into the second wallet (Wallet B) following a favorable match between the login credentials and the login details.

FIG. 6 shows a view that is displayed on the second user device 20 in FIG. 1B. The user is already logged into the wallet, as shown in the top right. The user can accept or decline an agreement. FIG. 7 displays the first page that is displayed to the user following acceptance of the agreement. The page shows the current balance corresponding to the

14

amount of bitcoin at the Bitcoin address (Bitcoin address 4) in FIG. 3. The user can select various tools down the left margin, including sending or requesting bitcoin, buying or selling bitcoin, account settings and various merchant tools. FIG. 8 illustrates a view that is displayed to the user if the user selects the "Buy/Sell" link in FIG. 7. The user is prompted to add a bank account. FIGS. 9 through 15 step the user through the entry of bank account details and verification of the bank account. The user can also select a credit card as a backup payment. FIGS. 16 to 19 step the user through the entry of a credit card number and a billing address, and FIGS. 20 and 21 step the user through a verification process to verify that the user is in control of the credit card account. FIGS. 22 and 23 request additional information from the user. FIG. 23 also allows the user to verify a phone at a phone number and FIGS. 24 through 27 step the user through a process for verifying their phone and phone number. FIGS. 28 through 30 illustrate a process for verifying an identity of the user of the second user device 20. As illustrated in FIGS. 31 to 33, the top margin within the account settings allow for additional tools such as referrals (FIG. 31), viewing of Bitcoin addresses (FIG. 32), and integration with an application programmable interface (FIG. 33).

FIG. 34 illustrates a process that is initiated by the user to purchase bitcoin from a wallet of the first host computer system 14. In the present example, the user selects one (1) bitcoin (BTC) to purchase. FIGS. 35 and 36 step the user through the process of purchasing the bitcoin. Once the bitcoin is purchased, the user can select on "History" tab in the top margin to display a view as shown in FIG. 37 wherein the transaction is displayed and is marked as "PENDING".

FIG. 38 shows an email that is transmitted by the hosted email module 46 in FIG. 1B to the second user device 20 to confirm the purchase of the bitcoin following selection of a "Confirm" button in FIG. 35. The email also has a link that, when selected by the user, opens the browser on the second user device 20 and allows the user to login to their wallet and view the transaction.

FIG. 39 shows an email that is transmitted by the hosted email module 46 in FIG. 1B to the second user device 20 with a notification that bitcoin has been added to their wallet as part of a referral bonus system.

FIG. 40 illustrates a view that is displayed when the user selects a "Limits and Verifications" tab in the top margin of the "Buy/Sell" page.

When the user selects the "Send/Request" link in the left margin in FIG. 40, the user is provided an option to send bitcoin from their wallet (Wallet B) in FIG. 3 to another wallet (e.g. the first wallet (Wallet A)) in FIG. 3.

FIG. 41 illustrates further transfers or purchases (Transfer 4; Transfer 5; Transfer 6). The fourth transfer (Transfer 4) represents the purchase of bitcoin from the first host computer system's 14 master wallet.

The fifth transfer (Transfer 5) represents the transfer of bitcoin from the second wallet (Wallet B) to the first wallet (Wallet A). The second wallet (Wallet B) now has login details stored therein. If the second user device 20 in FIG. 1B has been logged out of the second wallet (Wallet B), then the second user device 20 is first directed to the login module 38 which receives login details for the second wallet (Wallet B) from the second user device 20, verifies whether the login credentials for the second wallet (Wallet B) match the login details for the second wallet (Wallet B). If the login details match the login credentials, then the login module 38 logs the second user device 20 into the second wallet (Wallet B).

15

The login module **38** then provides the second user device **20** with access to the hosted email module **46**. The user of the second user device **20** then enters the email address (email address A) of the user of the first wallet (Wallet A) and an amount of bitcoin that the user of the second user device **20** wishes to transfer from the second wallet (Wallet B) to the first wallet (Wallet A). The user of the second user device **20** then uses the hosted email module **46** to send an email via the Internet **22** to the first user device **18**. As soon as the email is sent, a transfer (Transfer 5) is recorded within the second wallet (Wallet B). Because one of the Bitcoin addresses (Bitcoin address 4) has funds associated therewith, it can be charged for the transfer (Transfer 4). Within the second wallet (Wallet B) the transfer (Transfer 4) has the email address (email address A) to which the email has been sent and the amount in bitcoin associated therewith.

As indicated, the miner's fee that is paid by the first host computer system **14** and the host fee that is charged for the transfer are zero bitcoin because the first wallet (Wallet A) is stored within the wallets **42** of the first host computer system **14**. The user of the first user device **18** receives the email indicating the transfer of bitcoin to their wallet (Wallet A). A Bitcoin address (Bitcoin address 5) is recorded within the first wallet (Wallet A) for the transfer (Transfer 5) together with the identifier of the second wallet (Wallet B) from which the transfer has been made and the amount in bitcoin. The amount in bitcoin corresponding to the transfer (Transfer 4) in the second wallet (Wallet B) is the same as the amount in bitcoin as in the first wallet (Wallet A).

As illustrated by the next transfer (Transfer 6), the user of the second wallet (Wallet B) can opt to send bitcoin to a Bitcoin address of the first wallet (Wallet A). The transfer (Transfer 6) is the same as the preceding transfer (Transfer 5) in all other respects.

FIG. **42** shows a view that is displayed to the user of the second user device **20** in FIG. **1B** in order to make the transfer from their wallet (Wallet B) to the first wallet (Wallet A). The view includes a field for the user to enter the email address (email address A) and fields for entering either an amount in bitcoin (BTC) or an amount in a local currency (USD-United States Dollar). The exchange rate between bitcoin and the local currency is shown in the top left corner. The view also includes a button "Send Money" which, when selected by the user, initiates the transfer of bitcoin.

FIG. **43** is a view that is displayed to the user indicating transactions that have been initiated or completed. The purchase of bitcoin discussed with reference to FIGS. **35** to **37** is shown as "PENDING". A block chain verification notice has to be broadcast by the miner computer system **28** and be received by the first host computer system **14** in FIG. **1A** before a determination is made to change the marker "PENDING" to "COMPLETE". The other transactions representing transfers between the first and second wallets (Wallet A and Wallet B) in FIG. **41** are shown as completed because they do not need block chain verification outside of the first host computer system **14**. No block chain verification notice is thus required for these transactions to be marked "COMPLETE". FIG. **44** shows a view that can be selected by the user by selecting a tab in the top margin wherein the user is shown the Bitcoin addresses associated with transactions that have been completed.

FIG. **45** illustrates a further transaction (Transfer 7) wherein bitcoin is transferred from the second wallet (Wallet B) to a third wallet (Wallet C) held by the second host computer system **16** in FIG. **1A**. The user of the second user device **20** enters a bitcoin address (Bitcoin address 6) that is located in the third wallet (Wallet C) and an amount of

16

bitcoin to be transferred to the third wallet (Wallet C). A transfer (Transfer 7) is recorded within the second wallet (Wallet B). Associated with the transfer (Transfer 7) are the Bitcoin address (Bitcoin address 6), the amount in bitcoin that is being transferred and a miner's fee that is charged for the transfer and has to be paid by the first host computer system **14** to the miner computer system **28** in FIG. **1A**. No fee is charged by the first host computer system **14** for a transfer to another Bitcoin address.

When the user of the second user device **20** in FIG. **1A** completes the purchase, a transfer instruction is created and is broadcast via the host node **30** to all remote nodes **32A-D** within the Bitcoin network **12**. The transfer instruction thus traverses the first node and the second remote node **32B** to reach the second host computer system **16**. The second host computer system **16** and all other computer systems connected to the remote nodes **32A-D** record the transfer (Transfer 7) with respect to the Bitcoin addresses (Bitcoin address 4; Bitcoin address 6). The transfer (Transfer 7) has associated therewith the amount in bitcoin.

The transfer instruction that results in the transfer (Transfer 5) thus results in no miner's fee being charged to and paid by the first host computer system **14**. No host fee is charged to the second wallet (Wallet B) because the transfer (Transfer 7) is made to another wallet (Wallet A) within the wallets **42** of the first host computer system **14**. By contrast, the transfer instruction that results in the transfer (Transfer 7) representing the transfer to the Bitcoin address (Bitcoin address 6) in the third wallet (Wallet C) results in a miner's fee that is paid by the first host computer system **14** to the miner computer system **28**. The miner computer system **28** is responsible for verifying transfers of bitcoin over the Bitcoin network **12**. In the present scenario, the miner computer system **28** verifies the transfer of bitcoin from the second wallet (Wallet B) to the third wallet (Wallet C).

Another transfer may comprise that bitcoin is sent to one of the nodes, e.g. node **32C**. The node **32C** could be a fourth user device which is owned by the recipient of the bitcoin transfer having its own bitcoin address.

FIG. **46** illustrates components that are used for cold storage of value of bitcoin, including a local storage **56**, a local controller **58**, a vault **64**, a splitter **66**, one or more encryption algorithms **68** and **70** and an offline distribution module **72**.

The vault **64** has a Bitcoin address **80** with a private key **79**. The private key **79** is, for purposes of illustration, shown as a nine digit sequence of characters that are provided to the splitter **66**. For purposes of illustration, the splitter **66** splits the nine digits of the private key **79** into seven overlapping codes (Codes 1 to 7). The encryption algorithm **68** encrypts the first code (Code 1) into an encrypted code (Encrypted Code 1). In a similar manner, the second code (Code 2) is encrypted by an encryption algorithm (not shown) into an encrypted code (Encrypted Code 2). Each one of the seven codes is encrypted into a separate encrypted code. A separate key may be used for each one of seven codes. Alternatively, a separate encryption algorithm may be used for each one of the seven codes.

Once all the codes have been encrypted, the offline distribution module **72** transmits each one of the encrypted codes (Encrypted Code 1 to 7) to a separate location. The locations are remote locations that are geographically separated from one another. The offline distribution module **72** may also be used to print one or more of the encrypted codes for paper delivery to respective remote locations.

FIG. **47** illustrates functioning of the offline distribution module **72** following distribution of the encrypted codes in

FIG. 46. The offline distribution module 72 removes the private keys 79 of the Bitcoin address 80 of the vault 64. The offline distribution module 72 also removes the private key 79 of the Bitcoin address 80 within the local storage 56.

As shown in FIG. 48, a local register 60 includes a plurality of wallets 42, one of which is shown. The wallet 42 has a plurality of Bitcoin addresses 74, 76 and 78 associated therewith. Each Bitcoin address 74, 76 and 78 has a respective value and a respective private key. The local controller 58 transfers the entire value of the Bitcoin addresses 76 and 78 into the vault 64. The value relating to the Bitcoin address 74 is not transferred into the vault 64. The local controller 58 calculates the total value of the Bitcoin addresses 76 and 78 that have been transferred into the vault 64 and records the total value in the local storage 56 in association with the Bitcoin address 80.

As shown in FIG. 49, following removal of the value of the Bitcoin addresses 76 and 78 within the wallet 42, the value of the Bitcoin addresses 76 and 78 are only held within the vault 64 and the local storage 56. The private key 79 is only held in a split and encrypted form at the distributed locations where the offline distribution module 72 in FIG. 46 has distributed them to. Unless access can be gained to the private key 79 that has now been split and distributed, it is not possible to access the value of the Bitcoin addresses 76 and 78. It is now possible for a user to which the wallet 42 is registered to use the Bitcoin address 74 for transacting with another user via the wallet management module 44 in FIG. 1B. The Bitcoin addresses 76 and 78 are not usable by the wallet management module 44 for purposes of transacting with another user at this time because their values, within the wallet 42, have been removed.

FIG. 50 shows how the private keys of the vault 64 and the Bitcoin addresses 76 and 78 that were removed in FIG. 46 are restored. Components that are provided for restoration include a plurality of restoration interfaces 82, 84 and 86, one or more decryption algorithms 88, 90 and 92 and an assembler 94. The holder of the first encrypted code (Encrypted Code 1) is called upon to enter the encrypted code into the restoration interface 82. The restoration interface 82 may for example be a web page with a field for entry of the first encrypted code. Alternatively, the restoration interface 82 may be an application programmable interface (API) and the first encrypted code can be entered into the API with or without human involvement.

In the given example, the second, third, fifth and sixth encrypted codes are not received at this time. The fourth and seventh encrypted codes are received through the restoration interfaces 84 and 86, similar to the first encrypted code.

The decryption algorithm 88 decrypts the first encrypted code (Encrypted Code 1) into the first code (Code 1). In the given example, the decryption algorithms 90 and 92 decrypt the fourth and seventh encrypted codes (Encrypted Code 4 and Encrypted Code 7) into the fourth and seventh codes (Code 4 and Code 7) respectively. In the given example, three codes are the minimum number of codes that are required in order to reassemble the private key 79. The minimum number of codes required for reassembly in FIG. 48 is thus less than the total number of codes into which the private key 79 has been split in FIG. 46. The assembler 94 assembles the private key 79 when the minimum number of codes has been received.

The private key 79 of the Bitcoin address 80 in the local storage 56 is used to access the vault 64. The local controller 58 then restores the private key 79 from the local storage

been restored is the same private key 79 that was previously associated with the Bitcoin address. Only upon confirmation from the block chain will it be possible to transfer the value from the vault 64 to the local register 60.

The local controller 58 restores the respective value of the Bitcoin addresses 76 and 78 in the vault 64 to the Bitcoin addresses 76 and 78 in the wallet 42. Because the values have been restored to the Bitcoin addresses 76 and 78 in the wallet 42 they are usable for transacting with other users.

FIGS. 51a to 51d illustrate the use of a "hot" wallet in combination with "cold storage". As shown in FIG. 51a, the wallet 42 has the Bitcoin addresses 74, 76, 78 and a further Bitcoin address 98, each having a respective value associated therewith. The local storage 56 has first, second and third Bitcoin addresses 80A to 80C for first, second and third vaults 64A to 64C, respectively. The Bitcoin addresses 76 and 78 form a first transfer set that is selected for cold storage. The Bitcoin addresses 74 and 98 form a first transacting set. The values of the Bitcoin addresses 76 and 78 of the first transfer set are transferred into the first vault 64A, as represented by "Value" in the first vault 64A.

The private key of the Bitcoin address 80A of the first vault 64A is then transferred into the local storage 56 and is stored in association with the first Bitcoin address 80A. As hereinbefore described with reference to FIG. 46, the private key of the Bitcoin address 80A in the local storage 56 is then split and distributed. As hereinbefore described with reference to FIGS. 47 and 48, the private keys of the Bitcoin address 80 and the value of the Bitcoin address 76 and 78 are then removed. It is then not possible for a user of the wallet 42 to use the Bitcoin address 76 and 78 for transacting with another user. The user can still transact with another user using the Bitcoin addresses 74 and 98 of the first transacting set because their values are still associated with them within the wallet 42.

FIG. 51b shows the Bitcoin addresses 76 and 78 within the wallet 42 with their values removed and the Bitcoin address 80A within the local storage 56 with its private key removed. The private key of the Bitcoin address 80B of second vault 64B is transferred into the local storage 56 and associated with the second Bitcoin address 80B within the local storage 56. The private key of the second Bitcoin address 80B in the local storage 56 is split and distributed and then removed from the local storage 56. The Bitcoin address 98 is selected as part of a second transfer set of one or more Bitcoin addresses. The value of the Bitcoin address 98 is transferred from the wallet 42 into the second vault 64B, as represented by "Value" in the second vault 64B. The value of the Bitcoin address 98 within the wallet 42 is thus removed. The user of the wallet 42 can now not use the Bitcoin address 98 for purposes of transacting with another user because the value of the Bitcoin address 98 has been removed from the wallet 42. The Bitcoin address 74 forms part of a second transacting set that may include one or more Bitcoin addresses that can be used for transacting with another user.

FIG. 51c shows the Bitcoin address 98 having its value removed and the second Bitcoin address 80B within the local storage 56 having its private key removed. At this stage it may be desirable to restore the values of the Bitcoin addresses 76 and 78. The private key of the first Bitcoin address 80A within the local storage 56 is restored to the vault 64 as hereinbefore described with reference to FIG. 50. The respective values of the Bitcoin addresses 76 and 78 are then restored from the vault 64A to the Bitcoin addresses 76 and 78 in the wallet 42. Because the values of the Bitcoin addresses 76 and 78 are restored within the wallet 42, the

19

Bitcoin addresses **76** and **78** of the first transfer set can, at least for the time being, be used together with the second transacting set for transacting with another user.

The same Bitcoin addresses **74**, **76**, **78** and **98** that are shown in FIG. **51a** are also shown in FIGS. **51b** and **51c**. It should be understood that the Bitcoin addresses may change between the figures. The system allows for the value that was previously associated with one Bitcoin address to be restored to another Bitcoin address if necessary.

As shown in FIG. **51d**, the first vault **64A** is discarded after the value therein is restored. The first Bitcoin address **80A** within the local storage **56** and the first vault **64A** will never be used again.

The Bitcoin address **78** is selected as a third transfer set. The private key of the Bitcoin address **80C** of the third vault **64C** is transferred into the local storage **56** and stored in association with a third Bitcoin address **80C**. The value of the Bitcoin address **78** is transferred from the wallet **42** to the third vault **64C**. The user of the wallet **42** can now not use the Bitcoin address **78** for transacting with another user. The Bitcoin address **76** forms part of a third transacting set that could include one or more Bitcoin addresses. The Bitcoin address **76** can be used by the user of the wallet **42** for transacting with another user because the value of the Bitcoin address **76** is associated therewith within the wallet **42**. The second and third transacting sets can thus be used by the user for transacting with another user. The second and third transfer sets are unusable for transacting with another user because their private keys have been removed.

FIG. **52** illustrates how the local controller **58** (see FIGS. **46** to **50**) maintains transaction sets of a wallet **42** within a target range **101**. Should all the Bitcoin addresses of the wallet **42** have values associated therewith, the wallet **42** is said to be 100% hot and 0% cold. If all the Bitcoin addresses in a wallet **42** have their values removed, the wallet **42** is to be 0% hot and 100% cold. The target range **101** for the total bitcoin value within the wallet may for example be 5% to 10% hot. At **102**, the values of the first transacting set are transferred from the wallet **42** as described with reference to FIG. **51a**. At **104**, the user transacts with some of the Bitcoin addresses and the total value within the wallet **42** of the Bitcoin addresses that are hot is reduced. At **106**, the values of the second transfer set are removed from the wallet **42** as described with reference to FIG. **51b**. At **108**, the values of the first transfer set are restored as described with reference to FIG. **51c**. At **110**, the user transacts and gains further Bitcoin addresses for additional value within their wallet **42**. At **112**, values of the third transfer set are transferred out of the wallet **42** as described with reference to FIG. **51d**. It can thus be seen that the local controller **58** in FIGS. **46** to **50** adjusts the total value of bitcoin that is not within the target range **101**. The local controller **58** typically recalculates the hot/cold value ratio of each wallet on a daily basis and automatically adjusts the value to the target range **101**.

FIG. **53** illustrates the use of an intermediate hot wallet **114** that is used to collect bitcoin values from a plurality of wallets **42A** to **C**. The wallet **42A** is that same as the wallet **42** as described above. The wallet **42B** has bitcoin addresses **120**, **122**, **124** and **126** associated therewith. The wallet **42C** has bitcoin addresses **128**, **130**, **132** and **134** associated therewith. Each wallet **42A**, **B** or **C** is held within the target range **101** in FIG. **50**. The values of the bitcoin addresses **76**, **78**, **120**, **122**, **128** and **130** are identified for transfer to the vault **64A** and are first transferred or "swept" to the intermediate hot wallet **114** from where they are transferred to the vault **64A**.

20

FIG. **54** illustrates a network environment **136** that, in addition to the first host computer system **14**, includes a customer computer system **138** and a merchant computer system **140** that are connected to one another over the Internet **142**. The merchant computer system **140** has an online store **144** and a website **146**. The customer computer system **138** has a browser **148**. A customer at the customer computer system **138** can use the browser **148** to access the website **136** over the Internet **142**. The website **136** is then displayed on the browser **148**. The website **136** allows for the customer to make purchase on the online store **144**. The customer may, for example, purchase real goods, virtual goods or services from the online store **144**.

The first host computer system **14** includes an application programmable interface (API) **150**, a reference code generator **152**, a transaction processor **154**, a currency converter **156** and merchant, and customer and host wallets **158**, **160** and **162**. The wallets **158**, **160** and **162** may be of the kind as hereinbefore described.

As shown in FIG. **55**, the customer is shown a shopping cart with several payment options, including "Pay with Credit Card" and "Pay with bitcoin." Prior to being displayed the shopping cart, the customer has traveled through the shopping flow of the merchant computer system **140**, has selected one or more items to be purchased and has selected a shopping or checkout cart, which causes the display of the view shown in FIG. **55**. When the user selects the button "Pay with bitcoin" the merchant computer system **140**, at **166**, transmits an API call to the first host computer system **14**. The API call includes a request for payment. The request for payment includes an amount in a currency, in the present example \$14.00, an order name (usually a number), order descriptions (usually items in the checkout cart in a single line-item entry separated by commas), and a success uniform resource locator (URL) if desired (a page to which the customer is redirected at checkout if the order completes).

When the first host computer system **14** receives the API call at **166**, the reference code generator **152** generates a unique reference code for the specific order. The reference code is thus uniquely generated for each API call. The first host computer system **14** then stores the reference code in its database. At **168**, the first host computer system **14** responds to the API call received at **166** to transmit the reference code to the merchant computer system **140**. The merchant computer system **140** then receives the reference code as reference code **170**. The merchant computer system **140** stores the reference code as reference code **172** within its accounting system **173** and associates the reference code **172** with the particular order shown in the shopping cart. The merchant computer system **140** also creates a URL **174**. The reference code **170** is used as a reference code **176** within the URL **174** when the URL **174** is created.

The first host computer system **14** creates a URL **180** that includes a reference code **182**. The reference code **182** and the reference code **176** are the same.

The merchant computer system **140** at **178** redirects the browser **148** (FIG. **54**) using the URL **174**. The browser is then redirected to the URL **180** of the first host computer system **14**.

The URL **180** may, for example, be the URL of a landing page, iFrame or modal window **184**. The landing page, iFrame or modal window **184** presents checkout options to the customer, including to pay with the customer wallet **160** if one exists, to pay with bitcoin using an external account, or to create a wallet at the first host computer system **14** for purposes of completing the purchase. In a different embodiment, instead of being automatically redirected by the mer-

21

chant computer system **140** to the first computer system **14**, the customer may be redirected to a different page at the merchant computer system **140**, which will then contain a link for the customer to navigate to the landing page, iFrame or modal window **184**.

When the browser **148** of the customer computer system **138** downloads the landing page, iFrame or modal window **184**, the first host computer system **14** automatically generates a bitcoin address **186** specifically for the customer's order within the merchant wallet **158**.

The first host computer system **14** also creates a bitcoin price based on the price in local currency and displays the bitcoin price within the landing page/iFrame or modal window **184** within the browser **148**. The graph illustrates a fluctuating bitcoin to dollar exchange rate. In the present example, the exchange rate at minute 0 is used at **190** to calculate the exchange rate. The local currency price in the present example is \$14.00 which gives a bitcoin price of 0.02 BTC. The price of 0.02 BTC that is based on the exchange rate at minute 0 is maintained for a select period of time, in the present example 10 minutes, before it resets. The customer may not wish to immediately send the bitcoin, but may do so at any time before the price resets at minute 10 and the exchange rate remains locked in and the bitcoin price thus remains unchanged at 0.02 BTC during that time.

An option is displayed to the customer to send the bitcoin together with the price in bitcoin at minute 0. When the customer selects the option to send the bitcoin, the customer computer system **138** transmits a send instruction to the first host computer system **14**. The first host computer system **14** receives and at **192** detects the send instruction. The customer may for example request to send bitcoin from the customer wallet **160** or via another path as hereinbefore described. The first host computer system **14** responds to the send instruction to transmit an order status message that includes the reference code for the transaction to the merchant computer system **140**. The merchant computer system **140** receives the reference code as reference code **194**. The merchant computer system **140** then matches the reference code **194** to the reference code **172** within its accounting system **173** and marks the transaction as complete.

In the present example, the send instruction is processed at minute 6. The exchange rate has in the present example changed between minute 0 and minute 6. Should the bitcoin price of 0.02 BTC be converted to local currency at this time it would result in a different price in local currency than the original transaction. The difference between the original price at minute 0 and minute 6 represents either a loss or a gain for the first host computer system **14**. The loss and gain is used to calculate bitcoin replacement costs on a periodic basis.

In the present example the first computer system **14** responds to the send instruction received at **192** to transmit 0.02 BTC to the bitcoin address **186** associated with the merchant wallet **158**. When the bitcoin reaches the bitcoin address **186**, the first host computer system **14**, at **196**, immediately purchases the bitcoin from the merchant wallet **158**, resulting in a transfer of the bitcoin from the merchant wallet **158** to the host wallet **162**. The first host computer system **14** purchases the bitcoin at the exchange rate locked in at minute 0.

Periodically, for example daily, the first host computer system **14** calculates the total amount of bitcoin sold by the merchant wallet **158** that day at the locked in prices. The first host computer system **14** has a bank transfer module **200** that, at **202**, transmits a payment instruction to a bank for the first host computer system **14**. The bank for the first host

22

computer system **14** communicates with a bank of the merchant computer system **140**. Such communication, at **204**, results in transfer of funds from a host bank account **206** to a merchant bank account **208**.

In the present example, the customer uses their customer wallet **160** to transfer funds in the form of bitcoin from the customer wallet **160** to the merchant wallet **158** and the funds are then transferred in the form of bitcoin from the merchant wallet **158** to the host wallet **162**. In another embodiment, the merchant wallet **158** can be bypassed such that the customer transfers funds in the form of bitcoin from the customer wallet **160** directly into the host wallet **162**. In either embodiment the funds that are received by the host wallet **162** are used as a basis for calculating the amount of money in local currency that is transferred by the bank transfer module **200**, minus a fee that is held back by the first host computer system **14** for purposes of processing the transaction.

Referring again to FIG. **54**, the API **150** sends and receives API calls at **166**, **168** and the order status message in response to the send instruction **192** in FIG. **55**. The currency converter **156** is responsible for receiving and maintaining exchange rate for bitcoin to local currency and for calculating the bitcoin price based on the local currency price and the exchange rate at any particular moment in time. The transaction processor **154** is responsible for transferring funds in the form of bitcoin or local currency from one wallet or bank account to another.

In the embodiment above, the exchange rate is locked in when the customer accesses the landing page, iFrame or modal window **184** and is locked for ten minutes. In such an embodiment the merchants typically create a payment "button" or using the API, specifically the button API, of the first host computer system. Selection of the button by the customer results from the process described above wherein the customer is directed to the landing page, iFrame or modal window **184**. Such a button does not need to look any different from the merchant's standard "submit order" button and the button API is linked into the standard "submit order" button of the merchant computer system **140**, which when clicked will direct the user directly to the landing page, iFrame or modal window **184**. When the user hits the landing page the exchange rate is locked. The merchant "order" is thus not created—i.e., with locked in exchange rate—until the user clicks the payment button to land on our landing page.

Another embodiment is used in white-label solutions. In these instances, the user is not directed away from the merchant domain to a landing page such as the landing page, frame or modal window **184** to complete payment. Instead, the checkout information that would have otherwise shown on the landing page is displayed inside the merchant's browser checkout tool. Such an embodiment may not allow "one-click" checkout for users who are already signed into their customer wallet **160**; a user can only pay by QR code scan and/or manual entry of a bitcoin address. In order for this information to be incorporated into the merchant's webpage, the merchant (1) creates a "button" when they post an item for sale to the website (the button includes the price in local currency, but not a bitcoin price and can be created at any time—e.g., weeks before a purchase); and (2) when the customer wishes to pay, e.g., by clicking on a "Place Order" button, the merchant computer system **140** sends an API call to the first host computer system **14** which responds by sending back a locked in exchange rate, which again is good for ten minutes. The merchant then displays the checkout information to the user—i.e., the proper bitcoin

23

address and amount. This embodiment differs in that: (1) the “order” is created earlier in time, and the exchange rate follows on as a separate API call; and (2) the checkout information is hosted within the merchant’s domain.

FIG. 56 illustrates a method of managing bitcoin wherein a personal vault is created for a user. At 220, the user already has an account that the user can log into using a website. The account has a first email (electronic communication) address. The first email address may be john.smith@gmail.com. The account also has a phone number associated therewith and one or more wallets as herein before described. The website provides the user with a link to create a vault. At 222, the user is provided an option to create an individual vault or a group vault. In an individual vault the user will be required to respond to two emails in order to transfer bitcoin out of the vault. In a group vault multiple users are required to respond to emails in order for the user of the account represented at 220 to transfer the bitcoin out of the vault.

The user may, at 224, select an individual vault. At 226, an interface of the website is presented with a field for the user to enter a second email address. The second email address may for example be john.smith@hotmail.com. The user enters the second email address and selects a button to transmit the second email address from their device to the first host computer system 14. When the first host computer system 14 receives the second email address, the first host computer system 14, at 228, transmits a confirmation email with a confirmation link to the second email address. The purpose of the email that is transmitted at 228 is to confirm the second email address. At 230, the first host computer system 14 waits for the confirmation. The first host computer system 14 does not proceed to create a vault if the confirmation is not received. At 232, the user selects the confirmation link, which causes transmission of the confirmation from the device of the user to the first host computer system 14. When the first host computer system 14 receives the confirmation, the first host computer system 14 proceeds at 232 to register a vault within the same account shown at 220. The vault includes the first and second email addresses. The vault also includes the phone number of the account.

At 236, the first host computer system 14 updates the interface of the website to provide a summary. The summary indicates that, in order to transfer bitcoin out of the vault, emails will be sent to the first and second email addresses, and the summary includes the phone number associated with the vault and that the bitcoin will not be transferred out of the vault for a period of 48 hours. The interface also includes a “Finish” button. When the user selects the “Finish” button, the browser used by the user, at 238, lands in the vault. The vault looks like a wallet, but has a security feature that limits transfer of bitcoin out of the vault.

The user may, at 240, select a group vault. At 242, the first host computer system 14 provides the user with an option whether 2 out of 3 confirmations are required or 3 out of 5 confirmations are required. If the user selects that 2 out of 3 confirmations are required, then the user is required to enter two email addresses in addition to their own email address shown in the account at 220. If the user selects that 3 out of 5 confirmations are required, then the user is required to enter four email addresses in addition to their email address shown in the account at 220.

At 224, the interface of the website is updated to request the additional email addresses from the user. The interface typically includes fields for the user to enter the additional email addresses.

24

At 246, the first host computer system 14 makes a determination whether all the additional email addresses are associated with other accounts within the first host computer system 14. If all the additional email addresses are associated with other accounts, then the first host computer system 14 proceeds at 248 to update the account represented at 220 with a vault that includes the first email address, the additional email addresses and the phone number associated therewith.

If one or more of the additional email addresses are not associated with any accounts within the first host computer system 14, then the first host computer system 14, at 250, transmits an email to the additional email address that is not associated with an account to create an account. A user receiving the email transmitted at 250 can proceed at 252 to create an account with the second email address associated with the account. Only after all the additional email addresses are associated with accounts does the first host computer system 14, at 248, proceed to register a vault.

The first host computer system 14 then at 254 provides a summary through the interface of the website. The summary shows that in order to transfer bitcoin, emails will be sent to and confirmations will be required from the first email address and the minimum of the additional email addresses. The summary also includes the phone number associated with the vault and states the waiting period before the bitcoin is transferred. The website also includes a “Finish” button which, when selected by the user at 238, lands the browser used by the user in the vault.

FIG. 57 illustrates how bitcoin is transferred into and out of the vault. At 260, the user first transfers bitcoin into the vault. The user may transfer the bitcoin from one of their wallets associated with their account into the vault or may transfer the bitcoin into the vault from an external source. The bitcoin is then stored within the vault.

At 262, the user requests a transfer out of the vault using the website. The user includes the amount of bitcoin to be transferred, the reason for the transfer and selects a wallet to which the bitcoin is to be transferred. The user also includes a two-factor code which the user may obtain through a mobile application or via SMS communication with the first host computer system 14.

At 264, the first host computer system 14 determines whether the two-factor code is correct. If the two-factor code is incorrect, then the first host computer system 14, at 266, makes no change to the website interface.

If the determination is made at 264 that the two-factor code is correct, then the first host computer system 14 proceeds at 268 to transmit all emails. In the case of an individual vault, emails are sent to the first and second email addresses represented in the account at 234 in FIG. 56. In the case of a group vault, then emails are transmitted to the first email address and the additional email addresses represented in the account at 248 in FIG. 56. At 270, the first host computer system 14 updates the transaction list within the website to represent that approval is being awaited.

Each one of the emails has a respective link that can be selected by a recipient. At 272, a user receiving one of the emails reacts to the email by clicking on the link. Selection of the link causes an authorization instruction to be transmitted from a device of the respective user to the first host computer system 14. At 274, the first host computer system 14 detects the authorization instruction received in response to one of the emails that have been transmitted. Selection of the link on the email opens a browser on the recipient’s device and displays a message that the authorization has been successfully approved.

25

At 276, the recipient of a second one of the emails reacts to the email by clicking the link on the second email to send an authorization instruction. At 278, the first host computer system 14 detects the authorization instruction transmitted at 276 and displays a web page indicating that the authorization has been successfully approved.

When all the predetermined approvals have been received, the first host computer system 14 proceeds, at 280, to update the transaction list to indicate that clearance is being awaited. At 282, only if the minimum number of approvals are detected, the first host computer system 14 starts a countdown timer and sends an email to the user of the account informing the user that the bitcoin will be transferred after 48 hours. Block 284 represents the transmission of three email reminders to the user during the 48 hour waiting period. Each email includes the time remaining before the 48 hours will have elapsed and the amount of bitcoin that will be transferred out of the vault. Each email also includes a "Cancel" link. The user can select the "Cancel" link, which caused the transmission of a cancel instruction to the first host computer system 14. The cancel instruction will cancel the transfer of the bitcoin and therefore the request that was transmitted at 262.

At 286, the first host computer system 14 detects an end of the time period. The first host computer system 14 then transfers the amount of bitcoin out of the vault and in to the destination selected at 262. The first host computer system 14 also updates the transaction list on the website to indicate that the transaction has been cleared.

FIG. 58 illustrates components of the first host computer system 14 that are used for carrying out the method shown in FIGS. 56 and 57, including an account 290 of a user, a website 292, a vault establishment wizard 294, a vault management module 296 and the transaction processor 154 hereinbefore described. The vault establishment wizard 294 is programmed to execute the establishment of the vault as described with reference to FIG. 56. The vault management module 296 is programmed to manage the vault as described with reference to FIG. 57. A user accesses the website 292 and downloads an interface so as to interact via the website 292 with the vault establishment wizard 294 and the vault management module 296. The vault management module 296 provides instructions to the transaction processor 154 to transfer the bitcoin out of the vault.

FIG. 59 shows the email that is transmitted at 228 in FIG. 56. FIG. 60 shows an interface of the website 292 in FIG. 58 when the user requests a transfer out of a vault at 262 in FIG. 57. FIGS. 61 and 62 show the emails that are transmitted at 268 in FIG. 57. FIG. 63 shows the interface of the website after the minimum number of approvals are received and the countdown clock has been started at 282 in FIG. 57.

Email addresses are used in the exemplary embodiment for electronic communication via email. Another embodiment may make use of other electronic communication addresses such as text messages to phone numbers or messages through social networks. Such messages may include authorization links as described or authorization may be obtained otherwise such as sending a reply message and including "Y" or "Yes" in the reply message. A secondary electronic communication address may be an individual address or a group address.

FIG. 64 illustrates the establishment of a user-controlled vault. At 302, a user at the first user device 18 transmits a request for a user-controlled vault to the first host computer system 14. At 304, the first host computer system 14 responds to the request to initiate key generation.

26

At 306, the first host computer system 14 generates a seed for a master key. At 308, the first host computer system 14 uses the seed generated at 306 to generate a master key. The master key includes a public key for the master key and a private key for the master key. At 310, the first host computer system 14 stores the public key for the master key and, at 312, stores the private key for the master key. The combination of the keys stored at 310 and 312 form a master key set 314.

A generation script 316 initially resides on the first host computer system 14. At 318, the first host computer system 14 transmits the generation script 316 to the first user device 18. The first user device 18 receives the generation script 316, which is executable on the first user device 18.

At 320, the generation script 316 generates a seed for a shared key. The generation script 316 includes a key generation algorithm. At 321, the key generation algorithm uses the seed generated at 320 to generate a shared key. The shared key includes a public key and a private key.

The private key for the shared key is shown at 322. The generation script 316 also includes an interface with a field for a user to enter a password via a keyboard. At 324, the user enters the password into the interface. The generation script 316 also includes an encryption algorithm. At 326, the encryption algorithm generates an encrypted seed from the private key shown at 322 and the password entered at 324.

At 328 and 330, the key generation algorithm and encryption algorithm respectively send the public key of the shared key and the encrypted seed to the first host computer system 14. At 332, the first host computer system 14 stores the public key for the shared key and, at 334, stores the encrypted seed for the shared key. The public key stored at 332 and the encrypted seed 334 can be viewed as a shared key set 336. Additionally, the private key shown at 322 forms part of the shared key set 336. The private key shown at 322 is however never transmitted from the first user device 18 to the first host computer system 14.

At 338, the generation script 316 further generates a seed for a user key. At 340, the key generation algorithm uses the seed generated at 338 to generate a user key. The user key includes a public key for the user key and a private key for the user key. At 342, the key generation algorithm transmits only the public key for the user key to the first host computer system 14. At 344, the first host computer system 14 stores the public key for the user key.

At 346, the generation script 316 displays the private key for the user key to the user. The user can then store the private key manually on the first user device 18 or write it down for later use. The first user device 18 never transmits the private key displayed at 346 to the first host computer system 14. The combination of the public key for the user key stored at 344 and the private key for the user key displayed at 346 form a user key set 348.

FIG. 65 illustrates how the user-controlled vault is used by the user. At 360, the user of the first user device 18 creates and transmits a request to transact using bitcoin of the user-controlled vault. At 362, the request reaches the transaction processor 154 hereinbefore described. At 364, the first host computer system 14 creates an authorization for the transaction.

The master key set 312, shared key set 336 and user key set 334 are replicated from FIG. 64 and the same reference numerals apply. It should however be understood that these keys are stored or displayed in FIG. 64 and that the stored and displayed keys are not stored but only retrieved and used in FIG. 65.

27

At 366, the first host computer system 14 signs the authorization 364 with the private key for the master key. Such signature then allows for an authorization to transact at 368. As shown in 370, two out of three authorizations are required in order to transact and the authorization provided at 368 may form one of the two authorizations.

A verification script 372 initially resides on the first host computer system 14. At 373, the first host computer system 14 initiates key collection by transmitting the verification script 372 to the first user device 18. The verification script 372 is executable on the first user device 18. Both the generation script 316 in FIG. 64 and the verification script 372 in FIG. 65 may be in the form of JavaScript™ that is executable by a browser on the first user device 18.

The encrypted seed stored at 334 on the first host computer system 14 is transmitted together with the verification script 372 and is received at 374 by the first user device 18. The verification script 372 further includes an interface with a field for entering a password. At 376, the user enters the same password that the user entered at 324 in FIG. 64 into the field provided in the interface using a keyboard. The verification script 372 further includes a decryption algorithm. At 378, the decryption algorithm uses the encrypted seed and the password to decrypt the encrypted seed and obtain the private key. The encryption at 326 in FIG. 64 and decryption at 378 in FIG. 65 may follow the BIP38 protocol which is commonly understood by those skilled in the art of bitcoin encryption.

The authorization 364 is transmitted together with the verification script 372 to the first user device 18. The verification script 372 further has a signature algorithm. At 380, the signature algorithm signs the authorization with the private key. The signature algorithm then transmits the signed authorization (together with the signature) to the first host computer system 14.

The first host computer system 14 has a verification module. As will be commonly understood as those skilled in the art, a verification module is an algorithm that verifies a signature that was created with a private key using a public key. At 382, the verification module verifies the signature using the same public key stored at 332 for the shared key in the shared key set 336 that also includes the encrypted seed stored at 334. At 384, the verification module determines whether the signature is correct. If the signature is not correct, then the first computer system 14 returns to 374 where the encrypted key is received and the user enters a password. If, at 384, a determination is made that the signature is correct, then the first host computer system 14 proceeds to 386 to provide an authorization due to the signature being correct. The authorization at 386 may be one of the authorizations required at 370 in order to authorize the transaction.

The verification script 372 further includes an interface for entering the private key of the user key that was previously displayed at 346 to the user. At 390, the user enters the private key into the field provided therefor. At 392, a signature algorithm forming part of the verification script 372 signs the authorization with the private key that has been entered by the user. The signature algorithm then transmits the signed authorization (together with the signature) to the first host computer system 14. At 394, a verification module verifies the signature using the public key that was stored at 344. At 396, the verification module determines whether the signature is correct. If the signature is incorrect, then the first host computer system 14 instructs the verification script 372 to return to 390 where the user is again asked for the private key for the user key. If the signature is correct, then the first

28

host computer system 14 proceeds to 398 to provide an authorization for the transaction due to the signature being correct. The authorization provided at 398 may be one of the authorizations required at 370.

What should be noted this time is that the password entered at 376 is never transmitted to the first host computer system 14. Similarly, the private key entered at 390 is never transmitted to the first host computer system 14. The user's control over the password and private key effectively disallows the transaction from being processed outside of the user's control.

After two out of the three authorizations have been received at 370, the first host computer system 14 proceeds at 400 to authorize the transaction with the transaction processor 154.

FIG. 66 illustrates an address generator 402 that is used to generate addresses such as the bitcoin address that are used for the transaction requested at 360 in FIG. 65. A master key seed 404, shared key seed 406 and user key seed 408 are generated. The master key seed 404 is used to generate a master public key 410 and a master private key 412. The shared key seed 406 is used to generate a shared public key 414 and a shared private key 416. The user key seed 408 is used to generate a user public key 418 and user private key 420.

Each one of the keys 410 to 420 may be used to generate child keys M/0, M/1 The shared keys at each level may then be combined to generate an address. For example, the M/0 keys of the master public key 410, shared public key 414 and user public key 418 may be used to generate an address (Address 0). The M/0 level may for example be the public keys stored at 310, 332 and 334 in FIG. 64. The address (Address 0) may for example be the bitcoin address for the transaction. Similarly, the M/1 level keys of the master public key 410, shared public key 414 and user public key 418 may be used to generate another address (Address 1). The further addresses may be generated to create further bitcoin addresses of for other purposes.

FIG. 67 of the accompanying drawings illustrates the first host computer system 14, a partner computer system 422 and a receiver computer system 424. The receiver computer system 424 includes a receiver browser 426. The partner computer system 422 has a website, in the present example a blog with a blog post 428 that has a blog post URL 430. At 432, a user of the receiver computer system 424 uses the receiver browser 426 to create the blog post 428.

The first host computer system 14 has a wallet in the form of receiver account 434, an embedded code generator and a button ID generator 438. At 440, the user of the receiver computer system 424 creates the receiver account 434. The receiver account 434 has login details 442 and a receiver account identifier (ID) 444. At 446, the user of the receiver computer system 424 logs into the receiver account 434 and enters the blog post URL 430 through the user interface 36 (FIG. 1B). The blog post URL 430 is then stored in association with the particular receiver account 434 with the wallet management module 44 (FIG. 1B). At 448, the first host computer system 14 provides the blog post URL 430 to the embedded code generator and button ID generator 438. The embedded code generator 438 then generates an embedded code 450 and, at 452, transmits the embedded code 450 to the receiver browser 426. The embedded code 450 includes the blog post URL 430, receiver account ID 444 and a startup caller 454.

The blog post 428 on the partner computer system 422 has a frame for pasting the embedded code 450 due to prior agreement between operators of the first host computer

system 14 and the partner computer system 422. At 456, the user of the receiver computer system 424 copies the embedded code 450 received at 452 and pastes the embedded code 450 into the frame of the blog post 428. The embedded code 450 is then embedded and forms part of the HyperText Markup Language (HTML) of the blog post 428.

A blog post 428 is used herein to describe the invention by way of example. It should however be understood that the invention may have broader application. A URL of a page may for example have a video, song or news article. Such a page will typically have a frame for pasting the embedded code 450. Alternatively, media content such as a video may not have a separate frame for pasting the embedded code. Instead, another manner of activating payment features of the invention may be provided, such as a separate URL link, voice activation, detection of human gestures of a user, etc.

The button ID generator (see 438) generates a unique button ID. At 458, the button ID generator stores the button ID as button ID 460 within a data store of the first host computer system 14. At 462, the button ID generator 438 stores the button ID 460 in association with the particular receiver account ID 444 and particular blog post URL 430. Multiple receiver accounts may exist within the first host computer system 14. In addition, a receiver account may have multiple blog post URL's associated therewith. Each pair of a respective receiver account ID and respective blog post URL have a unique button ID.

FIG. 68 shows the first host computer system 14, the partner computer system 422 and a sender computer system 464. The sender computer system 464 has a sender browser (not shown). At 466, the sender browser downloads the blog post 428 from the partner computer system 422. The startup caller 454 is a script, e.g. JavaScript®, that automatically executes on the sender computer system 464. At 470, the startup caller 454 retrieves all sender cookies 472 on the sender computer system 464. The startup caller 454, at 474, transmits a startup call to the first host computer system 14. The startup call includes the cookies 472, the blog post URL 430 and the receiver account ID 444.

The first host computer system 14 includes a startup call responder 476 that receives the startup call 474. The startup call responder 476, at 478, uses the blog post URL 430 and receiver account ID 444 received in the startup call 474 to identify the particular button ID 460.

The button ID 460 in storage may have bits 480 representing all payments made in association with the button ID 460. At 482, the startup call responder 476 retrieves the bits 480 associated with the button ID 460 from the data store.

At 483, the startup call responder 476 transmits a startup call response to the sender computer system 464. The startup call response transmitted at 483 is in response to the startup call received at 474. The startup call response includes a button 484, the bits 480, a session script 486 and the button ID 460. A display 490 of the sender computer system 464 displays the blog post 428. The embedded code 450 has added the button 484 and the bits 480 to the blog post 428. The button 484 is a two-dimensional button that is selectable by a user of the sender computer system 464. The session script 486 is associated with the button 484 so as to be executable when the user selects the button 484.

The embedded code 450, at 491, stores the button ID 460 within the sender cookies 472. The button ID 460 stored within the sender cookies 472 can now be used to identify the button ID 460 within the first host computer system 14.

In FIG. 69, the user has selected the button 484 which, at 492, initiates the session script 486. The session script 486, at 494, retrieves the sender cookies 472 and, at 496, makes

a session call to the first host computer system 14. The session call 496 includes the cookies 472.

The first host computer system 14 includes a session responder 498 that receives the session call 496. At 500, the session responder 498 checks all data for the button ID 460 that has been received in the session call 496. The data associated with the button ID 460 may include a bitcoin address 502, although no bitcoin address may be included within the cookies 472 of the session call 496. At 504, the session responder 498 determines whether a bitcoin address was received in the cookies 472 of the session call 496. If no bitcoin address was received, the first host computer system 14 executes a bitcoin address generator 506. The bitcoin address generator 506 then generates a bitcoin address and, at 508, stores the bitcoin address in association with the button ID 460. The newly saved bitcoin address is represented as bitcoin address 510. At 512, the session responder 498 transmits the bitcoin address 510 that has been generated by the bitcoin address generator 506 to the sender computer system 464. At 514, the session script 486 stores the bitcoin address 510 in association with the button ID 460 within the sender cookies 472. Upon a browser refresh, the process started at 466 in FIG. 68 is restarted and all cookies are stored from earlier browser sessions are collected and transmitted by the startup caller 454.

At 516, the session responder 498 determines whether the sender computer system 464 is signed into a sender account. The determination is made based on whether a signed-in cookie is found among the cookies transmitted in the session call 496. If no signed-in cookie is found, then the session responder 498 proceeds to 518. At 518, the session responder 498 sends a sign-in panel 520, a sign-in script 522, a listen code 524, a third party payment script 526, and a pull code 528 to the sender computer system 464. The session script 486 creates an overlay window that includes the sign-in panel 520 with a sign-in button 530 having the sign-in script 522 associated therewith. The user can select the sign-in button 530 which, at 532, initiates the sign-in script 522. The sign-in script 522 creates and opens a further window (not shown) that allows the sender of the sender computer system 464 to enter login details 534 of a sender account 536. At 540, the sign-in script 522 signs the sender computer system 464 into the sender account 536 using the login details 534. The sign-in script 522, at 548, stores a signed-in cookie 549 within the sender cookies 472. The sign-in panel 520 further includes two payment selections, including a third party wallet button 544, and a Quick Response (QR) code 546. The third party payment script 526 is stored in association with the third party wallet button 544. The listen code 524 and pull code 528 are stored in an executable manner within the sender computer system 464. The session script 486 retrieves the bitcoin address 510 from the sender cookies 472 and displays the bitcoin address 510 within the sign-in panel 520.

As shown in FIG. 70, if the determination at 516 is made that the sender computer system 464 is signed-in to the sender account 436, or after the sender computer system 464 signs-in at 540 in FIG. 69, the session responder 498 proceeds to 550. At 550, the session responder 498 transmits a signed-in panel 552, the listen code 524, the third party payment script 526, the pull code 528 and a host account payment script 554 to the sender computer system 464. The signed-in panel 552 is the same as the sign-in panel 520 with the exception that it includes a host account button 556 instead of the sign-in button 530. The third party payment script 526 is stored in association with the third party wallet

31

button **544**. The host account payment script **554** is stored in association with host account button **556**.

Selection by the user of the host account button **556** initiates at **560** the host account payment script **554**. The host account payment script **554** transmits an instruction to the transaction processor **154** of the selection. At **561**, the transaction processor **154** makes a payment out of the sender account **536** to the receiver account **434** as hereinbefore described without going through the bitcoin network or the block chain.

At **564**, the transaction processor **154** updates the bits **480** by adding the bits of the present transaction to the bits **480** already stored within the data store. The bits **480** within the data store thus represent an ongoing tally of all payments made in association with the button ID **460**. The bitcoin addresses **502** and **510** represent bitcoin addresses that are generated for different sender computer systems **464** using the same button ID **460**.

After the host account payment script **554** transmits the instruction to the transaction processor **154**, the host account payment script **554** initiates the pull code **528**. The pull code **528**, at **574**, pulls the new bit count from the bits **480** in the storage of the first host computer system **14**. At **566**, the pull code **528** updates the bits **480** in the blog post **428** based on the bits that have been pulled by the pull code **528** in FIG. **70**.

As shown in FIG. **71**, the user selects the third party wallet button **544** which, at **560**, causes execution of the third party payment script **526**. The third party payment script **526** then transmits a transaction (of bitcoin to the bitcoin address **510**) to a third party transaction processor **562**. The third party transaction processor **562** is hosted by a host computer system other than the first host computer system **14**. At **564**, the third party transaction processor **562** broadcasts the transaction to the bitcoin network **12** and it is picked up by the blockchain.

The first host computer system **14** further includes a block chain checker **567** and a bit updater **568**. The block chain checker **567**, at **570**, periodically checks the block chain. For purposes of this discussion, the block chain checker **567** checks the block chain to determine whether there are any new transactions for the bitcoin addresses **502** and **510** stored in association with the button ID **460**. If the block chain checker **567** finds any further transactions, the block chain checker **567** notifies the bit updater **568**. At **572**, the bit updater **568** updates the bits **480** that are associated with the respective bitcoin address **502** or **510**. The bits **480** are updated by adding bits for any new transactions that have been picked up by the block chain checker **567**.

At **574**, the bit updater **568** transmits a push update notification to the sender computer system **464**. The listen code **524** receives the push update notification. Websocket technology may for example be used for the push update notification in order to open an interactive communication link. The listen code **524** is continuously active and therefore continuously listens for push update notifications. When the listen code **524** receives the push update notification, the listen code **524** initiates the pull code **528**. The pull code **528**, at **574**, pulls the new bit count from the bits **480** in storage. At **566**, the pull code **528** updates the bits **480** in the blog post **428** based on the bits that have been pulled by the pull code **528** in FIG. **70**.

The QR code **546** may be scanned by an app on a mobile phone. The bitcoin address **510** is encoded in the QR code **546**. The app can decode the QR code **546** to extract the bitcoin address **510** and transmit a transaction (of bitcoin to

32

the bitcoin address **510**) to a third party transaction processor such as the third party transaction processor **562**.

The button **484** shown in FIG. **69** can be used as a Tip button. A user of the sender computer system **464** can use the button **484** to make a small discrete payment to the user of the receiver computer system **424**. Such a payment may, for example, be as a reward for the content of the blog post **428**.

FIG. **72** shows a system **600** for transacting bitcoin. An Internet interface **602** allows for user computers (user computers A to C) to connect to the system **600** over the Internet. Order gateways **604** are connected to the Internet interface **602** to receive buy and sell offers via the Internet interface **602** from the user computers A to C. A matching engine **606** is connected to the order gateways **604**. The matching engine **606** can receive the buy and sell offers from the order gateways **604**.

A feed generator **608** is connected to the Internet interface **602**. The matching engine **606** provides an output to a multicast pipeline **610**. The feed generator **608** is connected to the multicast pipeline **610**. The feed generator **608** receives the buy and sell offers from the multicast pipeline **610** and displays any buy and sell offers via the Internet interface **602** to the user computers A to C. Users can thus view any buy and sell offers already in the system before making their own buy and sell offers.

The matching engine **606** can match buy and sell offers and broadcast the matches to the multicast pipeline **610**. The feed generator **608** displays the matches via the Internet interface **602** to the user computers A to C.

An exchange database **612** includes records of bitcoin and currency held by users A to C corresponding to the user computers A to C. A clearing module **614** is connected to the multicast pipeline **610** and receives matches from the multicast pipeline **610**. An exchange **616** is connected to the clearing module **614**. The exchange **616** is also connected to the Internet interface **602**. Users at the user computers A to C can provide instructions via the Internet interface **602** to the exchange **616** to transfer bitcoin or currency. The exchange **616** has a number of functions, including calculating total amounts of bitcoin and currency as represented in the exchange database **612**, cross checking bitcoin and currency totals between the exchange database **612** and an exchange user **618**, transferring bitcoin and currency between wallets A to C that correspond respectively to the users A to C in the exchange database **612**, updating bitcoin and currency amounts of the users A to C in the exchange database **612**, and may receive and execute instructions from the clearing module **614** to transfer bitcoin and currency between the users A to C in the exchange database **612**.

The exchange is connected to a ledger **620**. The ledger **620** hold records of wallets A to C and further functions to cross-check balances between the exchange database **612** and exchange user **618**.

FIG. **73a** shows the beginning of a transfer-in algorithm that is executed by the system **600**. A user at user computer A has \$10 of currency in the exchange database **612**. For purposes of discussion, no other users have any bitcoin or currency. The exchange **616** calculates the total amount of currency and bitcoin within the exchange database **612** and records the total amount as \$10 and 0 bitcoin. The exchange user **618** has \$10, representing a previous transfer from wallet A to the exchange user **618**.

At **1a**, a user at user computer B requests a transfer via the Internet interface **602**. The transfer may for example be to transfer \$20 from wallet B to the exchange user **618**. At **1b**, the Internet interface **602** provides the transfer request to the exchange **616**. At **2a**, the exchange **616** sends a cross-check

33

request to the ledger 620 and at 2b the ledger 620 cross checks the totals in the exchange database 612 and the exchange user 618 before proceeding with a transfer. In the present example, the exchange database 612 has \$10 and 0 bitcoin and the exchange user 618 has \$10 and 0 bitcoin. The totals therefore match. If either the currency or bitcoin totals do not match, the exchange 616 does not make any further transfers and provides an alert to an operator. The operator will then remedy any mismatches and then reactivate the exchange 616. Because the totals match, the exchange 616 proceeds with the transfer.

As shown in FIG. 73b, the exchange 616, at 3, transfers \$20 from wallet B to the exchange user 618. The exchange user 618 calculates the total amount held by the exchange user 618 as \$30, representing the \$10 that was there before the transfer plus another \$20 because of the transfer.

At 4a, the exchange 616 records \$20 for user B in the exchange database 612. At 4b, the exchange 616 updates the totals and records a total amount of \$30, representing the \$10 held by user A and the \$20 that has been added for user B.

FIG. 73c illustrates the totals in the exchange database 612 and the exchange user 618 after a further transfer wherein a user at the user computer C has requested a transfer of 5 bitcoin from wallet C to the exchange user 618. The exchange user 618 now holds 5 bitcoin and \$30. User C, within the exchange database 612, now holds 5 bitcoin. The totals held with the exchange database 612 are \$30 and 5 bitcoin. For purposes of discussion, this ends the transfer-in algorithm that was started in FIG. 73a.

FIG. 73d shows a trading algorithm that is carried out after the transfer-in algorithm if FIGS. 73a to 73c. At 5a, a user (buyer) at user computer A submits a buy offer of 2 bitcoin at \$5 each (\$10 total). As noted previously, all offers are transmitted via the Internet interface 602, one of the order gateways 604, the matching engine 606 and the multicast pipeline 610 to the feed generator 608 which displays the offers on the Internet interface 602. A user at user computer C can thus see the buy offer submitted by the user at user computer A. At 5b, the user (seller) at user computer C submits a sell offer for 2 bitcoin at \$5 each to the Internet interface 602. At 5c, the buy and sell offers are submitted by the Internet interface 602 to one of the order gateways 604. At 5d, the order gateway 604 provides the buy and sell offers sequentially to the matching engine 606.

As mentioned, the user at user computer C can see the buy offer of the user at user computer A before submitting the sell offer. In another example, the user at user computer C can first submit the sell offer and the sell offer can be seen by the user at user computer A. The buy and sell offers will typically be received by the matching engine 606 at different times.

Multiple users may submit one or more buy and sell offers. The matching engine 606 attempts to match the buy and sell offers to one another. At 6, the matching engine 606 has matched the buy and sell offers received from users at the user computers A and C.

The matching engine 606 then provides a broadcast of the match over the multicast pipeline 610 discussed with reference to FIG. 72. At 7a, the feed generator 608 receives a multicast that includes the match. At 7b, the clearing module 614 receives the same multicast that includes the match. At 8, the feed generator 608 provides a feed to the Internet interface 602 that includes the match. As previously mentioned, the feed generator 608 also provides a feed of buy and sell offers to the Internet interface 602.

34

At 9a, the clearing module 614 updates user A within the exchange database 612 by adding 2 bitcoin and subtracting \$10 from user A. At 9b, the clearing module 614 updates user C by subtracting 2 bitcoin from and adding \$10 to user C. The clearing module 614 makes the updates directly to the exchange database 612.

There is no need for recalculating the totals within the exchange database 612 at this stage. The same amount of currency or bitcoin that has been subtracted from one user has been added to another user. The exchange database 612 thus still indicates totals of \$30 and 5 bitcoin.

FIG. 73e shows a withdrawal algorithm that can be carried out after the trading algorithm in FIG. 73d. At 10a, a user at user computer C requests a withdrawal of, for example, \$10. The request is received via the Internet interface 602 and is passed on to the exchange 616 at 10b.

At 11a, the exchange 616 sends a cross-check request to the ledger 620 and at 11b the ledger 620 cross checks the totals before proceeding. In the present example, the amount of bitcoin in the exchange user 618 and the total amount of bitcoin represented in the exchange database 612 are the same and the total currency amount in the exchange user 618 and in the exchange database 612 are the same. Should either of these two comparisons result in a mismatch, the exchange 616 will not make any withdrawal and create an alarm for an operator.

As shown in FIG. 73f, at 12, the exchange 616 transfers \$10 from the exchange user 618 to the wallet C. The exchange user 618 now has \$20, representing the \$30 in FIG. 73e minus the \$10 that has been transferred out. At 13a, the exchange 616 adds a representation for user C in the exchange database 612 showing a withdrawal of \$10. At 13b, the exchange 616 updates the totals. Because user C has made a withdrawal of \$10, the total currency amount within the exchange database 612 amounts to \$20. The amount of bitcoin is still the same. The total amounts in the exchange user 618 and in the exchange database 612 are thus the same.

Other users may submit similar withdrawal requests. For example, a user at user computer A may request a withdrawal of 1 bitcoin. The exchange 616 then cross checks the total amounts, makes a transfer of 1 bitcoin from the exchange user 618 to wallet A and updates the exchange database 612 by deducting 1 bitcoin from user A and updates the total amount of bitcoin to 4 bitcoin.

FIG. 74 shows a diagrammatic representation of a machine in the exemplary form of a computer system 900 within which a set of instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed. In alternative embodiments, the machine operates as a standalone device or may be connected (e.g., networked) to other machines. In a network deployment, the machine may operate in the capacity of a server or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine may be a personal computer (PC), a tablet PC, a set-top box (STB), a Personal Digital Assistant (PDA), a cellular telephone, a web appliance, a network router, switch or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term "machine" shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

The exemplary computer system 900 includes a processor 930 (e.g., a central processing unit (CPU)), a graphics

35

processing unit (GPU), or both), a main memory 932 (e.g., read-only memory (ROM), flash memory, dynamic random access memory (DRAM) such as synchronous DRAM (SDRAM) or Rambus DRAM (RDRAM), etc.), and a static memory 934 (e.g., flash memory, static random access memory (SRAM), etc.), which communicate with each other via a bus 936.

The computer system 900 may further include a video display 938 (e.g., a liquid crystal displays (LCD) or a cathode ray tube (CRT)). The computer system 900 also includes an alpha-numeric input device 940 (e.g., a keyboard), a cursor control device 942 (e.g., a mouse), a disk drive unit 944, a signal generation device 946 (e.g., a speaker), and a network interface device 948.

The disk drive unit 944 includes a machine-readable medium 950 on which is stored one or more sets of instructions 952 (e.g., software) embodying any one or more of the methodologies or functions described herein. The software may also reside, completely or at least partially, within the main memory 932 and/or within the processor 930 during execution thereof by the computer system 900, the memory 932 and the processor 930 also constituting machine readable media. The software may further be transmitted or received over a network 954 via the network interface device 948.

While certain exemplary embodiments have been described and shown in the accompanying drawings, it is to be understood that such embodiments are merely illustrative and not restrictive of the current invention, and that this invention is not restricted to the specific constructions and arrangements shown and described since modifications may occur to those ordinarily skilled in the art.

What is claimed:

1. A method comprising:

storing, by a local storage of a bitcoin host computer system, a first private key of a first vault Bitcoin address;

splitting, by the host computer system, the first private key of the first vault bitcoin address into a plurality of overlapping codes;

transmitting, by the host computer system, each code to a separate remote storage of a plurality of remote storages via a network interface device, wherein each remote storage stores a respective one of the received codes;

removing, by the host computer system, the first private key from the host computer system;

transferring, by the host computer system, a first bitcoin value of a first bitcoin address of a first wallet of a first user to the first vault bitcoin address such that the first bitcoin address has no bitcoin value after the transfer;

providing, by a first remote storage of the plurality of remote storages, a first one of the codes to the host computer system via a first restoration application programmable interface (API) of the host computer system;

providing, by a second remote storage of the plurality of remote storages, a second one of the codes to the host computer system via a second restoration API of the host computer system;

providing, by a third remote storage of the plurality of remote storages, a third one of the codes to the host computer system via a third restoration API of the host computer system;

36

receiving, by the host computer system, the first code, the second code and the third code via the first restoration API, the second restoration API and the third restoration API, respectively;

assembling, by the host computer system, the first private key of the first vault Bitcoin address by using each code and storing the first private key;

transferring, by the host computer system, the first bitcoin value from the first vault bitcoin address to the first bitcoin address of the first wallet by using the assembled first private key;

calculating, by the host computer system, that a first ratio of total bitcoin value within the first wallet to total bitcoin value within the first vault is above a target range;

automatically decreasing, by a local controller of the host computer system, the total bitcoin value within the first wallet to a new total bitcoin value that results in a calculated second ratio of total bitcoin value within the first wallet to total bitcoin value within the first vault that is within the target range, wherein automatically decreasing the total bitcoin value within the first wallet comprises:

identifying, by the local controller, a set of bitcoin addresses within the first wallet with appropriate associated values of bitcoin,

transferring, by the local controller, the associated values of bitcoin from the identified set of bitcoin addresses within the first wallet to an intermediate wallet, and

transferring, by the local controller, the value of bitcoin from the intermediate wallet to the first vault;

transacting, by the host computer system, bitcoin value from an address of the first wallet;

calculating, by the host computer system, that a third ratio of total bitcoin value within the first wallet to total bitcoin value within the first vault is below the target range;

automatically increasing, by the local controller, the total bitcoin value within the first wallet to a new total bitcoin value that results in a fourth calculated ratio of total bitcoin value within the first wallet to total bitcoin value within the first vault that is within the target range, wherein automatically increasing the total bitcoin value within the first wallet comprises:

assembling, by an assembler of the bitcoin host computer system, the first private key of the first vault bitcoin address by using the first code, the second code, and the third code received via respective restoration APIs, and

transferring, by the bitcoin host computer system, value of at least the first vault bitcoin address to at least one bitcoin address of the first wallet, by using the assembled first private key.

2. The method of claim 1, further comprising the host computer system communicating with a first user device of the first user via the Internet.

3. The method of claim 2, further comprising the host computer system communicating with a plurality of user devices via the Internet.

4. The method of claim 1, wherein the host computer system includes the first wallet, and wherein the first wallet is a hot wallet, wherein the first wallet includes a plurality of bitcoin addresses, wherein the host computer system includes a first vault, and wherein the first vault includes a plurality of bitcoin addresses including the first vault bitcoin address.

37

5. A system comprising:
 a remote node of a Bitcoin network;
 a bitcoin host computer system that includes a local controller, a first wallet of a first user and a first vault of the first user;
 a plurality of remote storages;
 a host node of the Bitcoin network that is communicatively coupled to the host computer system,
 wherein a local storage of the host computer system stores a first private key of a first vault bitcoin address of the first vault,
 wherein the host computer system splits the first private key of the first vault bitcoin address into a plurality of overlapping codes,
 wherein the host computer system transmits each code to a separate remote storage of the plurality of remote storages via a network interface device of the host computer system,
 wherein each remote storage stores a respective one of the received codes,
 wherein the host computer system removes the first private key from the host computer system,
 wherein the host computer system transfers a first bitcoin value of a first bitcoin address of the first wallet to the first vault bitcoin address such that the first bitcoin address has no bitcoin value after the transfer,
 wherein a first remote storage of the plurality of remote storages provides a first one of the codes to the host computer system via a first restoration application programmable interface (API) of the host computer system,
 wherein a second remote storage of the plurality of remote storages provides a second one of the codes to the host computer system via a second restoration API of the host computer system,
 wherein a third remote storage of the plurality of remote storages provides a third one of the codes to the host computer system via a third restoration API of the host computer system,
 wherein the host computer system receives the first code, the second code and the third code via the first restoration API, the second restoration API and the third restoration API, respectively,
 wherein the host computer system assembles the first private key of the first vault bitcoin address by using each code and storing the first private key,
 wherein the host computer system transfers the first bitcoin value from the first vault bitcoin address to the first bitcoin address of the first wallet by using the assembled first private key,

38

wherein the host computer system transacts bitcoin value from an address of the first wallet,
 wherein the host computer system periodically calculates a ratio of total bitcoin value within the first wallet to total bitcoin value within a first vault,
 wherein, in response to the calculated ratio being above a target range, the local controller automatically decreases the total bitcoin value within the first wallet to a new total bitcoin value that results in a new calculated ratio of total bitcoin value within the first wallet to total bitcoin value within the first vault that is within the target range, wherein the local controller automatically decreasing the total bitcoin value within the first wallet comprises:
 identifying a set of bitcoin addresses within the first wallet with appropriate associated values of bitcoin,
 transferring the associated values of bitcoin from the identified set of bitcoin addresses within the first wallet to an intermediate wallet, and
 transferring the value of bitcoin from the intermediate wallet to the first vault,
 wherein, in response to the calculated ratio being below the target range, the local controller automatically increases the total bitcoin value within the first wallet to a new total bitcoin value that results in a new calculated ratio of total bitcoin value within the first wallet to total bitcoin value within the first vault that is within the target range, wherein the local controller automatically increasing the total bitcoin value within the first wallet comprises:
 assembling the first private key of the first vault bitcoin address by using the first code, the second code, and the third code received via respective restoration APIs, and
 transferring value of at least the first vault bitcoin address to at least one bitcoin address of the first wallet, by using the assembled first private key.

6. The system of claim 5, wherein the host computer system is communicatively coupled to a first user device of the first user via the Internet.

7. The system of claim 6, wherein the host computer system is communicatively coupled to a plurality of user devices via the Internet.

8. The system of claim 5, wherein the first wallet is a hot wallet, wherein the first wallet includes a plurality of bitcoin addresses, and wherein the first vault includes a plurality of bitcoin addresses including the first vault bitcoin address.

* * * * *